



US008600526B2

(12) **United States Patent**
Nielsen et al.

(10) **Patent No.:** **US 8,600,526 B2**
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **MARKING DEVICE DOCKING STATIONS HAVING MECHANICAL DOCKING AND METHODS OF USING SAME**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Steven E. Nielsen**, North Palm Beach, FL (US); **Curtis Chambers**, Palm Beach Gardens, FL (US); **Jeffrey Farr**, Jupiter, FL (US)

3,988,922	A	11/1976	Clark et al.
4,623,282	A	11/1986	Allen
4,899,293	A	2/1990	Dawson et al.
4,989,151	A	1/1991	Nuimura
5,150,295	A	9/1992	Mattingly
5,214,757	A	5/1993	Mauney et al.
5,293,911	A	3/1994	Akeel
5,299,300	A	3/1994	Femal
5,329,464	A	7/1994	Sumic et al.
5,379,045	A	1/1995	Gilbert et al.

(73) Assignee: **CertusView Technologies, LLC**, Palm Beach Gardens, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 867 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/571,401**

CA	2623761	10/2008
CA	2623466	6/2011

(22) Filed: **Sep. 30, 2009**

(Continued)

(65) **Prior Publication Data**

US 2010/0084532 A1 Apr. 8, 2010

OTHER PUBLICATIONS

3M Dynatel, Brochure, 2006, 1-4.

(Continued)

Related U.S. Application Data

(60) Provisional application No. 61/102,115, filed on Oct. 2, 2008.

Primary Examiner — Anthony Haughton

(51) **Int. Cl.**
H05K 5/00 (2006.01)
H05K 7/00 (2006.01)
G06F 1/16 (2006.01)
G05B 19/18 (2006.01)

(57) **ABSTRACT**


Docking stations and docking methods are provided for use with marking devices used for marking the presence or absence of an underground facility in a dig area. The docking station may serve as a home base for storage of a marking device, for charging the battery of a marking device, for transferring data to and from a marking device, and for securing a marking device against unauthorized use and/or theft. The docking station may be a mobile docking station that is installed in a vehicle or may be a fixed docking station that is installed at a central location in the field, at a central office, at a home base facility, and the like.

(52) **U.S. Cl.**
USPC **700/58**; 361/679.01; 361/679.02;
700/56

(58) **Field of Classification Search**
USPC 361/679.01, 679.02, 679.33, 679.35,
361/679.41; 700/2, 56.58; 345/179; 404/94;
710/13

See application file for complete search history.

23 Claims, 22 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,381,338 A	1/1995	Wysocki	7,319,387 B2	1/2008	Willson et al.
5,389,149 A	2/1995	Carey et al.	7,372,247 B1	5/2008	Giusti et al.
5,467,271 A	11/1995	Abel et al.	7,400,976 B2	7/2008	Young et al.
5,486,067 A	1/1996	Huynh	7,443,154 B1	10/2008	Merewether et al.
5,490,646 A	2/1996	Shaw	7,451,721 B1	11/2008	Garza et al.
5,517,419 A	5/1996	Lanckton	7,482,973 B2	1/2009	Tucker et al.
5,529,433 A *	6/1996	Huynh et al. 404/94	7,532,127 B2	5/2009	Holman et al.
5,553,407 A	9/1996	Stump	7,636,901 B2	12/2009	Munson
5,659,985 A	8/1997	Stump	7,640,105 B2	12/2009	Nielsen et al.
5,673,050 A	9/1997	Moussally et al.	7,664,530 B2	2/2010	Skelton
5,689,415 A	11/1997	Calotycho et al.	7,733,077 B1	6/2010	Merewether et al.
5,699,244 A	12/1997	Clark, Jr.	7,773,095 B1	8/2010	Badrak et al.
5,704,142 A	1/1998	Stump	7,834,801 B2	11/2010	Waite et al.
5,734,348 A	3/1998	Aoki et al.	7,834,806 B2	11/2010	Tucker et al.
5,751,450 A	5/1998	Robinson	7,889,124 B2	2/2011	Islam et al.
5,769,370 A	6/1998	Ashjaee	7,889,888 B2	2/2011	Deardorr
5,819,859 A	10/1998	Stump et al.	7,929,981 B2	4/2011	Sangberg
5,848,373 A	12/1998	Delorme et al.	7,978,129 B2	7/2011	Sawyer et al.
5,918,565 A	7/1999	Casas	7,986,246 B2	7/2011	Angelis et al.
6,026,135 A	2/2000	McFee et al.	8,081,112 B2	12/2011	Tucker et al.
6,037,010 A	3/2000	Kahmann et al.	8,106,660 B1	1/2012	Merewether et al.
6,053,260 A	4/2000	Boon	8,118,192 B2	2/2012	Daugherty
6,064,940 A	5/2000	Rodgers	8,144,245 B2	3/2012	Vik
6,074,693 A	6/2000	Manning	8,155,390 B2	4/2012	Nielsen et al.
6,075,481 A	6/2000	Eslambolchi et al.	8,260,489 B2	9/2012	Nielsen et al.
6,079,114 A	6/2000	Toews	8,264,409 B2	9/2012	Miller
6,095,081 A	8/2000	Gochenour	8,280,969 B2	10/2012	Nielsen et al.
6,119,376 A	9/2000	Stump	8,296,308 B2	10/2012	Nielsen et al.
6,138,906 A	10/2000	DeMayo	8,311,765 B2	11/2012	Nielsen et al.
6,140,798 A	10/2000	Krieger	8,424,486 B2	4/2013	Nielsen et al.
6,188,392 B1 *	2/2001	O'Connor et al. 345/179	2002/0035432 A1	3/2002	Kubica et al.
6,240,360 B1	5/2001	Phelan	2002/0053608 A1	5/2002	Zeck et al.
6,282,477 B1	8/2001	Gudat et al.	2002/0103625 A1	8/2002	Card et al.
6,285,911 B1 *	9/2001	Watts et al. 700/2	2002/0115472 A1	8/2002	Andress
6,292,108 B1	9/2001	Straser et al.	2002/0122000 A1	9/2002	Bradley et al.
6,294,022 B1	9/2001	Eslambolchi et al.	2002/0130906 A1	9/2002	Miyaki
6,299,934 B1	10/2001	Manning	2002/0146272 A1	10/2002	Conover
6,320,518 B2	11/2001	Saeki et al.	2003/0012411 A1	1/2003	Sjostrom
RE37,574 E	3/2002	Rawlins	2003/0058164 A1	3/2003	Zhdanov et al.
6,360,931 B1	3/2002	Morford	2003/0080897 A1	5/2003	Tranchina
6,375,038 B1	4/2002	Daansen et al.	2003/0100316 A1	5/2003	Odamura
6,388,629 B1	5/2002	Albats et al.	2003/0135328 A1	7/2003	Burns et al.
6,390,336 B1	5/2002	Orozco	2003/0168834 A1	9/2003	Ulrich
6,401,051 B1	6/2002	Merriam	2003/0196585 A1	10/2003	McDonald et al.
6,437,708 B1	8/2002	Brouwer	2004/0006425 A1	1/2004	Wood
6,438,239 B1	8/2002	Kuechen	2004/0051368 A1	3/2004	Caputo
6,477,588 B1 *	11/2002	Yerazunis et al. 710/13	2004/0057795 A1	3/2004	Mayfield et al.
6,512,478 B1	1/2003	Chien	2004/0070535 A1	4/2004	Olsson et al.
6,526,400 B1	2/2003	Takata	2004/0124988 A1	7/2004	Leonard et al.
6,557,738 B1	5/2003	Meintzer	2004/0210370 A1	10/2004	Gudat
6,650,293 B1	11/2003	Eslambolchi	2004/0220731 A1	11/2004	Tucker
6,658,148 B1	12/2003	Fung	2004/0225444 A1	11/2004	Young et al.
6,686,910 B2	2/2004	O'Donnell	2005/0023367 A1	2/2005	Reighard
6,700,526 B2	3/2004	Witten	2005/0034074 A1	2/2005	Munson
6,710,741 B2	3/2004	Tucker	2005/0038825 A1	2/2005	Tarabzouni
6,723,375 B2	4/2004	Zeck et al.	2005/0040222 A1	2/2005	Robinson
6,751,552 B1	6/2004	Minelli	2005/0054457 A1	3/2005	Eyestone et al.
6,751,553 B2	6/2004	Young	2005/0150399 A1	7/2005	Wiley
6,778,128 B2	8/2004	Tucker et al.	2005/0156600 A1	7/2005	Olsson
6,798,379 B2	9/2004	Tucker et al.	2005/0192727 A1	9/2005	Shostak et al.
6,825,793 B2	11/2004	Taylor, Jr. et al.	2005/0206562 A1	9/2005	Willson et al.
6,833,795 B1	12/2004	Johnson et al.	2005/0232475 A1	10/2005	Floeder
6,850,161 B1	2/2005	Elliott et al.	2006/0026020 A1	2/2006	Waite et al.
6,898,525 B1	5/2005	Minelli	2006/0055584 A1	3/2006	Waite et al.
6,904,361 B1	6/2005	Tallman et al.	2006/0077095 A1	4/2006	Tucker et al.
6,941,890 B1	9/2005	Cristo et al.	2006/0085133 A1	4/2006	Young
6,947,028 B2	9/2005	Shkolnikov	2006/0085396 A1	4/2006	Evans
6,956,564 B1 *	10/2005	Williams 345/179	2006/0169776 A1	8/2006	Hornbaker
6,972,698 B2	12/2005	Deguchi	2006/0220955 A1	10/2006	Hamilton
6,973,291 B1	12/2005	Bellows	2006/0262963 A1	11/2006	Navulur
6,975,942 B2	12/2005	Young et al.	2006/0276198 A1	12/2006	Michelon et al.
6,999,021 B2	2/2006	Taylor, Jr.	2006/0276985 A1	12/2006	Xu
7,009,399 B2	3/2006	Olsson et al.	2006/0282191 A1	12/2006	Gotfried
7,048,320 B2	5/2006	Rubel et al.	2006/0282280 A1	12/2006	Stotz et al.
7,269,002 B1	9/2007	Turner et al.	2006/0289679 A1	12/2006	Johnson et al.
			2007/0031042 A1	2/2007	Simental
			2007/0040558 A1	2/2007	Overby et al.
			2007/0219722 A1	9/2007	Sawyer, Jr.
			2007/0223803 A1	9/2007	Shindo

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0268110	A1	11/2007	Little	2010/0188215	A1	7/2010	Nielsen et al.
2007/0286021	A1	12/2007	Hoemmans et al.	2010/0188216	A1	7/2010	Nielsen et al.
2008/0010009	A1	1/2008	Miyoshi	2010/0188245	A1	7/2010	Nielsen et al.
2008/0013940	A1	1/2008	Jung	2010/0188407	A1	7/2010	Nielsen et al.
2008/0084212	A1	4/2008	Wieland	2010/0189312	A1	7/2010	Nielsen et al.
2008/0180322	A1	7/2008	Islam	2010/0189887	A1	7/2010	Nielsen et al.
2008/0204322	A1	8/2008	Oswald et al.	2010/0198663	A1	8/2010	Nielsen et al.
2008/0208415	A1	8/2008	Vik	2010/0201690	A1	8/2010	Nielsen et al.
2008/0245299	A1	10/2008	Nielsen et al.	2010/0201706	A1	8/2010	Nielsen et al.
2008/0255795	A1	10/2008	Shkolnikov	2010/0205031	A1	8/2010	Nielsen et al.
2008/0310721	A1	12/2008	Yang	2010/0205032	A1	8/2010	Nielsen et al.
2009/0004410	A1	1/2009	Thomson et al.	2010/0205264	A1	8/2010	Nielsen et al.
2009/0013928	A1	1/2009	Nielsen et al.	2010/0205536	A1	8/2010	Nielsen et al.
2009/0063258	A1	3/2009	Mueller et al.	2010/0205554	A1	8/2010	Nielsen et al.
2009/0109081	A1	4/2009	Ryerson	2010/0205555	A1	8/2010	Nielsen et al.
2009/0121933	A1	5/2009	Tucker et al.	2010/0207816	A1	8/2010	Islam et al.
2009/0149894	A1	6/2009	Merry et al.	2010/0211354	A1	8/2010	Park et al.
2009/0171616	A1	7/2009	Zhang et al.	2010/0228588	A1	9/2010	Nielsen et al.
2009/0185858	A1	7/2009	Malit	2010/0245086	A1	9/2010	Nielsen et al.
2009/0201178	A1	8/2009	Nielsen et al.	2010/0247754	A1	9/2010	Nielsen et al.
2009/0201311	A1	8/2009	Nielsen et al.	2010/0253511	A1	10/2010	Nielsen et al.
2009/0202101	A1	8/2009	Nielsen et al.	2010/0253513	A1	10/2010	Nielsen et al.
2009/0202110	A1	8/2009	Nielsen et al.	2010/0253514	A1	10/2010	Nielsen et al.
2009/0202111	A1	8/2009	Nielsen et al.	2010/0255182	A1	10/2010	Nielsen et al.
2009/0202112	A1	8/2009	Nielsen et al.	2010/0256825	A1	10/2010	Nielsen et al.
2009/0204238	A1	8/2009	Nielsen et al.	2010/0256912	A1	10/2010	Nielsen et al.
2009/0204466	A1	8/2009	Nielsen et al.	2010/0256981	A1	10/2010	Nielsen et al.
2009/0204614	A1	8/2009	Nielsen et al.	2010/0257029	A1	10/2010	Nielsen et al.
2009/0204625	A1	8/2009	Nielsen et al.	2010/0257477	A1	10/2010	Nielsen et al.
2009/0207019	A1	8/2009	Nielsen et al.	2010/0259381	A1	10/2010	Nielsen et al.
2009/0208642	A1	8/2009	Nielsen et al.	2010/0259414	A1	10/2010	Nielsen et al.
2009/0210098	A1	8/2009	Nielsen et al.	2010/0262470	A1	10/2010	Nielsen et al.
2009/0210245	A1	8/2009	Wold	2010/0262670	A1	10/2010	Nielsen et al.
2009/0210284	A1	8/2009	Nielsen et al.	2010/0263591	A1	10/2010	Nielsen et al.
2009/0210285	A1	8/2009	Nielsen et al.	2010/0272885	A1	10/2010	Olsson
2009/0210297	A1	8/2009	Nielsen et al.	2010/0285211	A1	11/2010	Nielsen et al.
2009/0210298	A1	8/2009	Nielsen et al.	2010/0318401	A1	12/2010	Nielsen et al.
2009/0237408	A1	9/2009	Nielsen et al.	2010/0318402	A1	12/2010	Nielsen et al.
2009/0238414	A1	9/2009	Nielsen et al.	2010/0318465	A1	12/2010	Nielsen et al.
2009/0238415	A1	9/2009	Nielsen et al.	2010/0324967	A1	12/2010	Nielsen et al.
2009/0238416	A1	9/2009	Nielsen et al.	2011/0006772	A1	1/2011	Olsson
2009/0238417	A1	9/2009	Nielsen et al.	2011/0007076	A1	1/2011	Nielsen et al.
2009/0241045	A1	9/2009	Nielsen et al.	2011/0020776	A1	1/2011	Nielsen et al.
2009/0241046	A1	9/2009	Nielsen et al.	2011/0022433	A1	1/2011	Nielsen et al.
2009/0324815	A1	12/2009	Nielsen et al.	2011/0035245	A1	2/2011	Nielsen et al.
2009/0327024	A1	12/2009	Nielsen et al.	2011/0035251	A1	2/2011	Nielsen et al.
2010/0002365	A1	1/2010	Mulcahey	2011/0035252	A1	2/2011	Nielsen et al.
2010/0006667	A1	1/2010	Nielsen et al.	2011/0035260	A1	2/2011	Nielsen et al.
2010/0010862	A1	1/2010	Nielsen et al.	2011/0035324	A1	2/2011	Nielsen et al.
2010/0010863	A1	1/2010	Nielsen et al.	2011/0035328	A1	2/2011	Nielsen et al.
2010/0010882	A1	1/2010	Nielsen et al.	2011/0040589	A1	2/2011	Nielsen et al.
2010/0010883	A1	1/2010	Nielsen et al.	2011/0040590	A1	2/2011	Nielsen et al.
2010/0045517	A1	2/2010	Tucker et al.	2011/0045175	A1	2/2011	Nielsen et al.
2010/0070347	A1	3/2010	Chen	2011/0046993	A1	2/2011	Nielsen et al.
2010/0085054	A1	4/2010	Nielsen et al.	2011/0046994	A1	2/2011	Nielsen et al.
2010/0085185	A1	4/2010	Nielsen et al.	2011/0046999	A1	2/2011	Nielsen et al.
2010/0085376	A1	4/2010	Nielsen et al.	2011/0060496	A1	3/2011	Nielsen et al.
2010/0085694	A1	4/2010	Nielsen et al.	2011/0060549	A1	3/2011	Nielsen et al.
2010/0085701	A1	4/2010	Nielsen et al.	2011/0093162	A1	4/2011	Nielsen et al.
2010/0086671	A1	4/2010	Nielsen et al.	2011/0093304	A1	4/2011	Nielsen et al.
2010/0086677	A1	4/2010	Nielsen et al.	2011/0093306	A1	4/2011	Nielsen et al.
2010/0088031	A1	4/2010	Nielsen et al.	2011/0095885	A9	4/2011	Nielsen et al.
2010/0088032	A1	4/2010	Nielsen et al.	2011/0117272	A1	5/2011	Nielsen et al.
2010/0088134	A1	4/2010	Nielsen et al.	2011/0131081	A1	6/2011	Nielsen et al.
2010/0088135	A1	4/2010	Nielsen et al.	2011/0137769	A1	6/2011	Nielsen et al.
2010/0088164	A1	4/2010	Nielsen et al.	2011/0191058	A1	8/2011	Nielsen et al.
2010/0090700	A1	4/2010	Nielsen et al.	2011/0236588	A1	9/2011	Nielsen et al.
2010/0090858	A1	4/2010	Nielsen et al.	2011/0249394	A1	10/2011	Nielsen et al.
2010/0094553	A1	4/2010	Nielsen et al.	2011/0279229	A1	11/2011	Nielsen et al.
2010/0097224	A1	4/2010	Prodanovich	2011/0279230	A1	11/2011	Nielsen et al.
2010/0117654	A1	5/2010	Nielsen et al.	2011/0279476	A1	11/2011	Nielsen et al.
2010/0131903	A1	5/2010	Thomson et al.	2011/0283217	A1	11/2011	Nielsen et al.
2010/0146454	A1	6/2010	Sugahara	2011/0285749	A1	11/2011	Nielsen et al.
2010/0161359	A1	6/2010	Asher	2012/0019380	A1	1/2012	Nielsen et al.
2010/0188088	A1	7/2010	Nielsen et al.	2012/0036140	A1	2/2012	Nielsen et al.
				2012/0065924	A1	3/2012	Nielsen et al.
				2012/0065944	A1	3/2012	Nielsen et al.
				2012/0066137	A1	3/2012	Nielsen et al.
				2012/0066273	A1	3/2012	Nielsen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0066506	A1	3/2012	Nielsen et al.
2012/0069178	A1	3/2012	Nielsen et al.
2012/0072035	A1	3/2012	Nielsen et al.
2012/0110019	A1	5/2012	Nielsen et al.
2012/0113244	A1	5/2012	Nielsen et al.
2012/0274476	A1	11/2012	Nielsen et al.
2012/0328162	A1	12/2012	Nielsen et al.
2012/0330849	A1	12/2012	Nielsen et al.
2013/0002854	A1	1/2013	Nielsen et al.
2013/0006718	A1	1/2013	Nielsen et al.
2013/0044918	A1	2/2013	Nielsen et al.
2013/0085670	A1	4/2013	Nielsen et al.

FOREIGN PATENT DOCUMENTS

CH	695087	A5	12/2005
EP	1679232	A1	7/2006
JP	7256169		10/1994
JP	7128061		5/1995
JP	8285601		11/1996
JP	10060865		3/1998
JP	2000501666		2/2000
JP	2002079167		3/2002
WO	WO 9516827		6/1995
WO	WO 0194016		12/2001
WO	WO-0228541		4/2002
WO	WO-2008112461	A1	9/2008

OTHER PUBLICATIONS

3M Dynatel, Locating and Marking System, Brochure, 2007, 1-16.

Bernold, L., et al. "Equipment operator training in the age of internet2," Proceedings of 19th International Symposium on Automation and Robotics in Construction (ISARC 2002), Sep. 2002 [retrieved on Nov. 12, 2010]. Retrieved from the Internet: <URL: <http://fire.nist.gov/bfrlpubs/build02IPDF/b02059.pdf>>. p. 4, col. 2, para 2.

U.S. Appl. No. 13/644,226, filed Oct. 3, 2012, Nielsen et al.

European Search Report, Application No. 08743671.3, Nov. 16, 2011.

European Search Report, Application No. 08743673.9, Feb. 28, 2011.

International Search Report and Written Opinion, Application No. PCT/US10/45161, Oct. 29, 2010.

International Search Report and Written Opinion, Application No. PCT/US10/45409, Nov. 18, 2010.

International Search Report and Written Opinion, Application No. PCT/US10/45969, Nov. 18, 2010.

International Search Report and Written Opinion, Application No. PCT/US11/23208, Mar. 25, 2011.

International Search Report and Written Opinion, Application No. PCT/US2009/003957, Mar. 21, 2011.

International Search Report and Written Opinion, Application No. PCT/US2010/036029, Sep. 3, 2010.

International Search Report and Written Opinion, Application No. PCT/US2011/047807, Dec. 6, 2011.

Jung, H.G., Structure Analysis Based Parking Slot Marking Recognition for Semi-automatic Parking System, Springer-Verlag Berlin Heidelberg 2006, 10 pages.

Luczak, S., "Increasing Accuracy of Tilt Measurements," Engineering Mechanics, vol. 14, 2007, p. 143-154.

New Mexico's Recommended Marking Guidelines for Underground Utilities, May 2006, 8 pages.

Notice of Allowance dated Jan. 24, 2012 from U.S. Appl. No. 12/363,951.

Notice of Allowance dated Mar. 9, 2012 from U.S. Appl. No. 12/236,688.

Notice of Allowance dated May 2, 2012 from U.S. Appl. No. 12/429,929.

Notice of Allowance dated Jul. 12, 2012 from U.S. Appl. No. 12/539,497.

Notice of Allowance dated Aug. 1, 2012 from U.S. Appl. No. 12/364,339.

Notice of Allowance dated Sep. 5, 2012 from U.S. Appl. No. 12/854,370.

Notice of Allowance dated Oct. 1, 2012 from U.S. Appl. No. 12/607,843.

Notice of Allowance dated Oct. 17, 2012 from U.S. Appl. No. 12/236,688.

Notice of Allowance dated Oct. 25, 2012 from U.S. Appl. No. 12/639,373.

Notice of Allowance dated Nov. 7, 2012 from U.S. Appl. No. 12/639,041.

Notice of Allowance dated Apr. 28, 2011 from U.S. Appl. No. 29/356,631.

Notice of Allowance dated Jan. 25, 2012 from Canadian Application No. 2,710,189.

Notice of Allowance dated Nov. 12, 2010 from U.S. Appl. No. 29/356,633.

Notice of Allowance dated Nov. 12, 2010 from U.S. Appl. No. 29/356,634.

Notice of Allowance dated Nov. 12, 2010 from U.S. Appl. No. 29/356,635.

Notice of Allowance dated Nov. 28, 2011 from Canadian Application No. 2,710,269.

Office Action dated Jan. 12, 2012 from U.S. Appl. No. 12/364,369.

Office Action dated Jan. 25, 2012 from U.S. Appl. No. 12/568,087.

Office Action dated Feb. 1, 2011 from Canadian Application No. 2,691,707.

Office Action dated Feb. 9, 2012 from U.S. Appl. No. 12/364,339.

Office Action dated Feb. 28, 2012 from U.S. Appl. No. 12/539,497.

Office Action dated Mar. 2, 2012 from U.S. Appl. No. 12/639,041.

Office Action dated Mar. 13, 2012 from U.S. Appl. No. 12/364,359.

Office Action dated Mar. 20, 2012 from U.S. Appl. No. 12/764,164.

Office Action dated Mar. 29, 2012 from GB Application No. 1107052.1.

Office Action dated Apr. 10, 2012 from U.S. Appl. No. 12/854,370.

Office Action dated Apr. 12, 2012 from Canadian Application No. 2,691,707.

Office Action dated Apr. 13, 2012 from Australian Application No. 2008236526.

Office Action dated Apr. 17, 2012 from U.S. Appl. No. 12/607,843.

Office Action dated Apr. 25, 2012 from U.S. Appl. No. 12/363,046.

Office Action dated May 1, 2012 from Australian Application No. 2009300362.

Office Action dated May 15, 2012 from U.S. Appl. No. 12/797,243.

Office Action dated May 17, 2012 from U.S. Appl. No. 12/364,369.

Office Action dated May 24, 2011 from U.S. Appl. No. 12/363,951.

Office Action dated Jun. 1, 2012 from U.S. Appl. No. 12/855,977.

Office Action dated Jun. 4, 2012 from U.S. Appl. No. 12/568,087.

Office Action dated Jun. 4, 2012 from U.S. Appl. No. 12/703,958.

Office Action dated Jun. 8, 2012 from U.S. Appl. No. 12/639,041.

Office Action dated Jun. 13, 2012 from U.S. Appl. No. 12/639,373.

Office Action dated Jun. 18, 2012 from U.S. Appl. No. 12/701,468.

Office Action dated Jun. 18, 2012 from U.S. Appl. No. 12/701,496.

Office Action dated Jul. 2, 2012 from U.S. Appl. No. 12/797,262.

Office Action dated Jul. 12, 2012 from U.S. Appl. No. 12/571,411.

Office Action dated Jul. 26, 2012 from U.S. Appl. No. 12/639,041.

Office Action dated Jul. 27, 2012 from European Application No. 08743671.3.

Office Action dated Aug. 15, 2012 from Australian Application No. 2010214104.

Office Action dated Aug. 17, 2012 from Australian Application No. 2009300313.

Office Action dated Aug. 29, 2012 from U.S. Appl. No. 12/701,447.

Office Action dated Sep. 4, 2012 from U.S. Appl. No. 12/622,768.

Office Action dated Sep. 21, 2012 from U.S. Appl. No. 12/797,202.

Office Action dated Sep. 25, 2012 from Australian Application No. 2010214053.

Office Action dated Sep. 26, 2011 from Canadian Application No. 2,739,119.

Office Action dated Sep. 26, 2011 from Canadian Application No. 2,739,320.

Office Action dated Oct. 4, 2011 from U.S. Appl. No. 12/364,359.

(56)

References Cited

OTHER PUBLICATIONS

- Office Action dated Oct. 15, 2012 from U.S. Appl. No. 12/797,227.
 Office Action dated Oct. 19, 2012 from U.S. Appl. No. 12/797,243.
 Office Action dated Oct. 20, 2011 from U.S. Appl. No. 12/639,041.
 Office Action dated Oct. 24, 2011 from U.S. Appl. No. 12/236,688.
 Office Action dated Nov. 15, 2011 from Canadian Application No. 2,691,707.
 Office Action dated Dec. 30, 2011 from U.S. Appl. No. 12/701,447.
 Office Action dated Jul. 20, 2010 from U.S. Appl. No. 11/696,606.
 Office Action dated Jul. 11, 2011 from Canadian Application No. 2713282.
 Office Action dated Jun. 28, 2011 from Canadian Application No. 2710269.
 Office Action dated Mar. 3, 2011 from Australian Application No. 2008226627.
 Office Action dated Mar. 9, 2011 from Australian Application No. 2008236526.
 Office Action dated Oct. 6, 2010 from Canadian Application No. 2623761.
 Olsson, Office Action dated Sep. 13, 2012 from U.S. Appl. No. 12/827,993.
 Product Data, Hard Hat Aerosols Marking Paint 2300; Rust-oleum Netherlands B.V., Apr. 2005, 1 page, <http://www.rustoleum.co.uk/downloads/2300%20Marking%20Spray.pdf>.
 Product Data, "Inverted Marking Chalk," Rust-oleum, Jul. 2004, 2 pages, http://www.policeone.com/pdfs/markingschalkinfo_ro.pdf.
 Virginia Underground utility marking standard, Mar. 2004, 20 pages.
 U.S. Appl. No. 13/751,862, filed Jan. 28, 2013, Nielsen et al.
 U.S. Appl. No. 13/795,337, filed Mar. 12, 2013, Nielsen et al.
 U.S. Appl. No. 13/797,229, filed Mar. 12, 2013, Nielsen et al.
 U.S. Appl. No. 13/834,382, filed Mar. 15, 2013, Nielsen et al.
 U.S. Appl. No. 13/846,120, filed Mar. 18, 2013, Nielsen et al.
 U.S. Appl. No. 13/867,521, filed Apr. 22, 2013, Nielsen et al.
 Corrected Notice of Allowability dated May 13, 2013 from U.S. Appl. No. 12/429,929.
 Corrected Notice of Allowability dated May 14, 2013 from U.S. Appl. No. 12/797,202.
 Corrected Notice of Allowability dated May 10, 2013 from U.S. Appl. No. 12/797,227.
 Corrected Notice of Allowability from U.S. Appl. No. 12/364,369 dated Apr. 15, 2013.
 Corrected Notice of Allowability from U.S. Appl. No. 12/703,958 dated Apr. 18, 2013.
 Notice of Allowance dated Apr. 25, 2013 from U.S. Appl. No. 12/364,359.
 Notice of Allowance dated May 10, 2013 from U.S. Appl. No. 12/797,243.
 Office Action dated Mar. 13, 2013 from Chinese Application No. 201080045879.1.
 Office Action dated Apr. 26, 2013 from U.S. Appl. No. 12/859,394.
 Office Action dated May 10, 2013 from U.S. Appl. No. 12/786,929.
 Corrected Notice of Allowability from U.S. Appl. No. 12/622,768 dated Apr. 3, 2013.
 Corrected Notice of Allowability from U.S. Appl. No. 12/797,202 dated Apr. 4, 2013.
 Corrected Notice of Allowability from U.S. Appl. No. 12/797,227 dated Apr. 17, 2013.
 Notice of Allowance dated Jan. 22, 2013 from U.S. Appl. No. 12/703,958.
 Notice of Allowance dated Feb. 1, 2013 from U.S. Appl. No. 12/797,202.
 Notice of Allowance dated Feb. 13, 2013 from U.S. Appl. No. 12/701,447.
 Notice of Allowance dated Feb. 20, 2013 from U.S. Appl. No. 12/364,369.
 Notice of Allowance dated Mar. 28, 2013 from U.S. Appl. No. 12/797,227.
 Notice of Allowance dated Jan. 24, 2013 from U.S. Appl. No. 12/622,768.
 Notice of Allowance dated Mar. 12, 2013 from U.S. Appl. No. 12/429,929.
 Office Action dated Feb. 26, 2013 from Canadian Application No. 2,738,968.
 Office Action dated Mar. 20, 2013 from U.S. Appl. No. 12/764,164.
 Office Action dated Mar. 25, 2013 from U.S. Appl. No. 12/797,211.
 Office Action dated Mar. 28, 2013 from U.S. Appl. No. 12/571,408.
 International Search Report and Written Opinion, Application Serial No. PCT/US2009/005401, Jun. 18, 2010, 18 pages.
 GPS Technology Enhancing Underground Utility Locating, Underground Construction Magazine, Apr. 2010, 3 pages.
 International Search Report and Written Opinion, Application Serial No. PCT/2010/000389, 11 pages.
 Office Action dated Jun. 16, 2010 from Canadian Application No. 2,691,707, filed Feb. 10, 2010.
 Co-pending U.S. Appl. No. 12/571,408, filed Sep. 30, 2009.
 Co-pending U.S. Appl. No. 12/571,411, filed Sep. 30, 2009.
 International Search Report (Partial), Application Serial No. PCT/US2009/005401.
 International Search Report and Written Opinion, Application Serial No. PCT/US2008/55798, Jul. 28, 2008.
 U.S. Appl. No. 13/686,262, filed Nov. 27, 2012, Nielsen et al.
 Notice of Allowance dated Jun. 8, 2013 from U.S. Appl. No. 12/797,243.
 Notice of Allowance dated Dec. 12, 2012 from U.S. Appl. No. 12/703,958.
 Notice of Allowance dated Dec. 21, 2012 from U.S. Appl. No. 12/364,339.
 Office Action dated Jan. 9, 2013 from U.S. Appl. No. 12/571,411.
 Office Action dated Oct. 2, 2012 from Japanese Application No. 2010-502170.
 Office Action dated Nov. 14, 2012 from Canadian Application No. 2,750,908.
 Office Action dated Nov. 20, 2012 from U.S. Appl. No. 12/701,468.
 Office Action dated Nov. 21, 2012 from U.S. Appl. No. 12/701,496.
 Office Action dated Nov. 23, 2012 from U.S. Appl. No. 12/855,977.
 Office Action dated Nov. 26, 2012 from U.S. Appl. No. 12/764,164.
 Office Action dated Dec. 5, 2012 from U.S. Appl. No. 12/797,262.
 Office Action dated Dec. 18, 2012 from U.S. Appl. No. 12/786,929.
 Office Action dated Dec. 20, 2012 from U.S. Appl. No. 12/571,408.
 Office Action dated Dec. 28, 2012 from U.S. Appl. No. 12/364,359.
 Office Action received Jun. 18, 2013 from Japanese Application No. 2009-553688.
 European Search Report dated Oct. 9, 2013 from European Application No. 13177282.4.
 Examination Report dated Sep. 4, 2013 from European Application No. 10732529.2.
 Notice of Allowance dated Aug. 27, 2013 from U.S. Appl. No. 12/855,977.
 Notice of Allowance dated Sep. 17, 2013 from U.S. Appl. No. 12/859,394.
 Notice of Allowance dated Sep. 25, 2013 from U.S. Appl. No. 12/364,369.
 Notice of Allowance dated Sep. 25, 2013 from U.S. Appl. No. 12/571,408.
 Office Action dated Aug. 7, 2013 from Canadian Application No. 2,739,119.
 Office Action dated Aug. 7, 2013 from Canadian Application No. 2,739,320.
 Office Action dated Sep. 9, 2013 from U.S. Appl. No. 13/867,521.
 Office Action dated Sep. 25, 2013 from U.S. Appl. No. 13/686,262.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C

Method 700




FIG. 9




FIG. 10




FIG. 11

Method 1000




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

Docking station network 1600




FIG. 20

Docking station network 1700




FIG. 21

1

MARKING DEVICE DOCKING STATIONS HAVING MECHANICAL DOCKING AND METHODS OF USING SAME

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority based on Provisional Application Ser. No. 61/102,115, filed Oct. 2, 2008, which is hereby incorporated by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates generally to the field of marking devices and, more particularly, to docking stations for use with marking devices and to methods of using the same.

BACKGROUND

Field technicians, such as land surveyors and utility location experts, often utilize marking material to identify a specific location on the ground. Conventional marking devices are used for dispensing a marking material, such as marking spray paint.

Existing marking devices are relatively inexpensive. Accordingly, the cost of individual marking devices is generally considered insignificant by the user of the marking device. Consequently, users may not take due care when handling such marking devices. As a result, marking devices are often mishandled, broken, or left behind in the field. As marking devices become more complex and incorporate additional functions, the devices become more costly. Therefore, approaches are needed in the marking industry to provide better ways of handling and keeping track of marking devices in the field. Similarly, as increased functionality is incorporated into marking devices, it is desirable to provide methods of managing data and power requirements of the marking devices in the field.

Further, users may carelessly stow marking devices in their vehicles. For example, users often toss marking devices into vehicles and leave them unsecured. In the event of a vehicle accident, the marking device may be thrown about the vehicle cab and cause injury to the passengers. Consequently, it is desirable to provide better methods of securing marking devices in vehicles.

Accordingly, approaches are needed for better ways of handling and tracking marking devices, securing marking devices in vehicles, and managing data and power requirements of marking devices.

SUMMARY OF THE INVENTION

The present invention relates generally to the field of marking devices used for marking the presence or absence of an underground facility in a dig area. More particularly, the invention relates to docking stations for use with such marking devices and to methods for using the docking station with a marking device. The docking station may serve as a home base for storage of a marking device, for charging the battery of a marking device, for facilitating data transfer to and from a marking device, and for securing a marking device against unauthorized use and/or theft. In some embodiments, the docking station may be a mobile docking station that is installed in a vehicle. In other embodiments, the docking station may be a fixed docking station that is installed in a central location in the field, at a central office, at a home base facility, and the like.

2

According to a first aspect of the invention, a docking station is provided for docking a marking device of the type used to mark the presence or absence of an underground facility in a dig area. The docking station comprises a housing configured to mechanically support a marking device in a docked position; and a security mechanism to secure the marking device in the docking station.

According to a second aspect of the invention, a method is provided for handling a marking device of the type used to mark the presence or absence of an underground facility in a dig area. The method comprises mechanically supporting a marking device in a docked position in a docking station; and securing the marking device in the docking station with a security mechanism.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects and features of the present invention are set forth with particularity in the appended claims. The present invention, both as to its organization and manner of operation, together with further objectives and advantages, may be best understood by reference to the following description, taken in connection with the accompanying drawings as set forth below:

FIG. 1 is a schematic design of a docking station and a marking device, with the marking device removed from the docking station, according to embodiments of the invention;

FIG. 2 is a schematic diagram of a marking device attached to a docking station;

FIG. 3A is a simplified block diagram of a system that includes an electronic docking station coupled to a marking device, in accordance with embodiments of the invention;

FIG. 3B is a simplified block diagram of a system that includes an electronic and mechanical docking station coupled to a marking device, in accordance with embodiments of the invention;

FIG. 3C is a simplified block diagram of a system that includes a mechanical docking station coupled to a marking device, in accordance with embodiments of the invention;

FIG. 4 is a schematic block diagram of docking station electronics, in accordance with embodiments of the invention;

FIG. 5A is a top view of a portion of a docking station;

FIG. 5B is a side view of a portion of a docking station;

FIG. 6A is a side view of a portion of a marking device that may be attached to a docking station;

FIG. 6B is a bottom view of a portion of a marking device that may be attached to a docking station;

FIG. 7 is a side view of a marking device being attached to a docking station;

FIG. 8A is a top view of an exemplary vehicle configuration incorporating a docking station;

FIG. 8B is a top view of another exemplary vehicle configuration incorporating a docking station;

FIG. 8C is a schematic block diagram of a network system incorporating a docking station;

FIG. 9 is a flow diagram of a method of using a docking station;

FIG. 10 is a flow diagram of another method of using a docking station;

FIG. 11 is a schematic diagram of a marking device attached to a docking station, according to another embodiment of the invention;

FIG. 12 is a flow diagram of an additional method of using a docking station;

FIG. 13 is a schematic diagram of an exemplary configuration incorporating docking stations;

FIG. 14 is a perspective view of an embodiment of a docking station and a marking device, with the marking device removed from the docking station;

FIG. 15 is an enlarged perspective view of a portion of the docking station and marking device of FIG. 14;

FIG. 16 is a perspective view of the docking station with the marking device docked therein;

FIG. 17 is a perspective view of a marking device docking station that has processing and communications capability, in accordance with embodiments of the invention;

FIG. 18 is a schematic diagram of multiple fixed marking device docking stations in communication with a central computing device, which is one example of a docking station network, in accordance with embodiments of the invention;

FIG. 19 is a schematic diagram of multiple mobile marking device docking stations in the field and in communication with an onsite computing device, which is another example of a docking station network, in accordance with embodiments of the invention;

FIG. 20 is a schematic diagram of multiple mobile marking device docking stations in the field and in communication with each other, which is yet another example of a docking station network, in accordance with embodiments of the invention; and

FIG. 21 is a schematic diagram of at least one marking device docking station in communication with at least one marking device, which is still another example of a docking station network, in accordance with embodiments of the invention.

DETAILED DESCRIPTION

The present invention relates to marking devices used for marking the presence or absence of an underground facility in a dig area and, more particularly, to docking stations for use with such marking devices. The present invention further includes methods for using docking stations with marking devices. By way of example, the docking station may serve as a home base for storage of a marking device and for charging the battery of a marking device. In some embodiments, the docking station may be a mobile docking station that is installed in a vehicle. In other embodiments, the docking station may be a fixed docking station that is installed at a central location in the field, at a central office, at a home base facility, and the like. The docking station may be used in a variety of locations that are convenient and/or accessible for a user, including worksites, and may be fixed or mobile depending on the configuration.

For purposes of the present disclosure, the term “dig area” refers to a specified area of a work site within in which there is a plan to disturb the ground (e.g., excavate, dig holes and/or trenches, bore, etc.), and beyond which there is no plan to excavate in the immediate surroundings. Thus, the metes and bounds of a dig area are intended to provide specificity as to where some disturbance to the ground is planned at a given work site. It should be appreciated that a given work site may include multiple dig areas.

The term “facility” refers to one or more lines, cables, fibers, conduits, transmitters, receivers, or other physical objects or structures capable of or used for carrying, transmitting, receiving, storing, and providing utilities, energy, data, substances, and/or services, and/or any combination thereof. The term “underground facility” means any facility beneath the surface of the ground. Examples of facilities include, but are not limited to, oil, gas, water, sewer, power, telephone, data transmission, cable television (TV), and/or internet services.

The term “locate device” refers to any apparatus and/or device for detecting and/or inferring the presence or absence of any facility, including without limitation, any underground facility. In various examples, a locate device may include both a locate transmitter and a locate receiver (which in some instances may also be referred to collectively as a “locate instrument set,” or simply “locate set”).

The term “marking device” refers to any apparatus, mechanism, or other device that employs a marking dispenser for causing a marking material and/or marking object to be dispensed, or any apparatus, mechanism, or other device for electronically indicating (e.g., logging in memory) a location, such as a location of an underground facility. Additionally, the term “marking dispenser” refers to any apparatus, mechanism, or other device for dispensing and/or otherwise using, separately or in combination, a marking material and/or a marking object. An example of a marking dispenser may include, but is not limited to, a pressurized can of marking paint. The term “marking material” means any material, substance, compound, and/or element, used or which may be used separately or in combination to mark, signify, and/or indicate. Examples of marking materials may include, but are not limited to, paint, chalk, dye, and/or iron. The term “marking object” means any object and/or objects used or which may be used separately or in combination to mark, signify, and/or indicate. Examples of marking objects may include, but are not limited to, a flag, a dart, and arrow, and/or an RFID marking ball. It is contemplated that marking material may include marking objects. It is further contemplated that the terms “marking materials” or “marking objects” may be used interchangeably in accordance with the present disclosure.

The term “locate mark” means any mark, sign, and/or object employed to indicate the presence or absence of any underground facility. Examples of locate marks may include, but are not limited to, marks made with marking materials, marking objects, global positioning or other information, and/or any other means. Locate marks may be represented in any form including, without limitation, physical, visible, electronic, and/or any combination thereof.

The terms “actuate” or “trigger” (verb form) are used interchangeably to refer to starting or causing any device, program, system, and/or any combination thereof to work, operate, and/or function in response to some type of signal or stimulus. Examples of actuation signals or stimuli may include, but are not limited to, any local or remote, physical, audible, inaudible, visual, non-visual, electronic, mechanical, electromechanical, biomechanical, biosensing or other signal, instruction, or event. The terms “actuator” or “trigger” (noun form) are used interchangeably to refer to any method or device used to generate one or more signals or stimuli to cause or causing actuation. Examples of an actuator/trigger may include, but are not limited to, any form or combination of a lever, switch, program, processor, screen, microphone for capturing audible commands, and/or other device or method. An actuator/trigger may also include, but is not limited to, a device, software, or program that responds to any movement and/or condition of a user, such as, but not limited to, eye movement, brain activity, heart rate, other data, and/or the like, and generates one or more signals or stimuli in response thereto. In the case of a marking device or other marking mechanism (e.g., to physically or electronically mark a facility or other feature), actuation may cause marking material to be dispensed, as well as various data relating to the marking operation (e.g., geographic location, time stamps, characteristics of material dispensed, etc.) to be logged in an electronic file stored in memory. In the case of a locate device or other locate mechanism (e.g., to physically locate a facility or other

feature), actuation may cause a detected signal strength, signal frequency, depth, or other information relating to the locate operation to be logged in an electronic file stored in memory.

The terms “locate and marking operation,” “locate operation,” and “locate” generally are used interchangeably and refer to any activity to detect, infer, and/or mark the presence or absence of an underground facility. In some contexts, the term “locate operation” is used to more specifically refer to detection of one or more underground facilities, and the term “marking operation” is used to more specifically refer to using a marking material and/or one or more marking objects to mark a presence or an absence of one or more underground facilities. The term “locate technician” refers to an individual performing a locate operation. A locate and marking operation often is specified in connection with a dig area, at least a portion of which may be excavated or otherwise disturbed during excavation activities.

The term “user” refers to an individual utilizing a locate device and/or a marking device and may include, but is not limited to, land surveyors, locate technicians, and support personnel.

The term “power source” refers to an apparatus, a device, a system, and/or any other means, and/or any combination thereof that generates, transmits, converts, and/or supplies power or energy, including, but not limited to, electrical power.

Reference is now made to the following description of embodiments of the present invention, which are illustrated in the accompanying figures. The same reference numbers in different drawings may identify the same or similar elements. In addition, the following detailed description does not limit the present invention.

A docking station **100** and a marking device **150**, removed from docking station **100**, are shown in the schematic diagram of FIG. 1. Docking station **100** may be installed in, for example, a vehicle and is suitable for use in conjunction with marking device **150**. In other embodiments, the docking station **100** may be installed at a central facility, office or other fixed location. Thus, the docking station **100** may be mobile or fixed. Docking station **100** may serve as a home base for storage of marking device **150** and for charging the battery of marking device **150**.

Docking station **100** may include a base **110** and a support housing **114**. Base **110** and support housing **114** may be made of any suitably strong, rigid, and lightweight material. Such material may include, but is not limited to, molded plastic and metal. Docking station **100** may be designed and constructed to be bolted to the body of a vehicle and may be made of materials that prevent unauthorized removal from a vehicle. In the embodiment of FIG. 1, docking station **100** is configured and mounted to support marking device **150** in an upright, or vertical, position. In other embodiments, docking station may be configured and mounted to support marking device **150** in a horizontal position or in any other position.

In an embodiment, a cradle **118** is integrated into the upper end of support housing **114**. This provides a mechanism to mechanically and electrically couple marking device **150** to docking station **100**. Other embodiments illustrating a cradle that may be integrated into support housing **114** are described with reference to FIGS. 5A, 5B, 6A, 6B, and 7.

Electronic and electro-mechanical components that provide an interface between a marking device, an external computing device, and/or a power source may be installed in support housing **114**. For example, docking control electronics **128**, including a communications interface **122** and a power interface **126**, may be installed in support housing **114**.

Communications interface **122** and power interface **126** may be the drive and buffer circuitry for supplying electrical signals and power, respectively, to cradle **118**, which in turn supplies electrical signals and power to marking device **150** when marking device **150** is attached to docking station **100**. In the embodiment of FIG. 1, communications interface **122** provides a wired connection to control electronics in marking device **150**. In other embodiments, docking station **100** may include a wireless link to control electronics in marking device **150**. Docking station **100** may supply electrical signals and power to any configuration or embodiment of marking device **150**, and marking device **150** may receive electrical signals and power from any configuration or embodiment of docking station **100**.

Docking control electronics **128** may include a processor and other circuitry for managing and driving various user interface devices, such as, but not limited to, indicators **130**, manual controls **134**, and audio output **138**. Docking station **100** may include visible and/or audible means of informing the user of status changes and other conditions requiring attention. Further, docking station **100** may include user controls that allow a user to initiate activities, such as data synchronization (e.g., uploading and downloading data). For example, indicators **130** may include one or more light-emitting diode (LED) devices of specified colors and indicate a meaning to the user (e.g., red, green, and yellow battery status indicators; yellow and orange data synchronization status indicators, and the like). Manual controls **134** may include one or more manual push buttons for initiating various functions (e.g., an initiate data synchronization push button). Audio output **138** may be, for example, an audio speaker, an audio alarm and/or buzzer. Docking control electronics **128** may include an audio input (not shown). For example, an audio input, such as a microphone, may be incorporated into the docking station.

Docking control electronics **128** may also include a mechanism for short range identification, such as radio-frequency identification (RFID). For example, docking station **100** may include an RFID reader **129** for reading an RFID tag affixed to marking device **150**. In another embodiment, docking station **100** may include a barcode reader for reading a barcode affixed to marking device **150**.

The processor of docking control electronics **128** may be capable of managing data transfer between marking device **150** and an external computing device. For example, a wired connection **140**, such as a universal serial bus (USB) connection, RS232 connectors, RJ45 connectors, Ethernet, and any combination thereof may be provided between docking control electronics **128** of docking station **100** and an external computing device. Further, the processor of docking control electronics **128** may be programmable to perform any user-defined function, such as, but not limited to, executing a security function programmed to ensure that only authorized personnel may access and use marking device **150** and/or docking station **100**. Additionally, a wired power connection (not shown) may be provided for connecting docking station **100** to the power source of a vehicle in which it is installed. The power source of a vehicle may be used to charge the battery of marking device **150**.

Additionally, a safety strap **142** for securing marking device **150** in docking station **100** may be attached to support housing **114** of docking station **100**. In one embodiment, a device, incorporated in safety strap **142**, is capable of conducting an electrical signal that may be detected by docking control electronics **128** to indicate whether safety strap **142** has been secured around marking device **150**. For example, a small tracer wire may be installed within safety strap **142**,

which changes a logic state depending upon whether both ends or one end only is fastened to support housing **114**. As described below, docking station **100** may include additional or different locking and security devices.

Marking device **150** may be any marking device that has, for example, battery powered electronics incorporated therein for any functionality (e.g., global positioning system (GPS) technology, RFID technology, data storage devices, electronic actuator, electronic display, marking material sensing technology, wired and/or wireless communications technology and the like). For example, marking device **150** may be a marking device as described in U.S. publication no. 2008-0228294-A1, published Sep. 18, 2008, filed Mar. 13, 2007, and entitled "Marking System and Method With Location and/or Time Tracking;" U.S. publication no. 2008-0245299-A1, published Oct. 9, 2008, filed Apr. 4, 2007, and entitled "Marking System and Method;" and U.S. publication no. 2009-0204238-A1, published Aug. 13, 2009, filed Feb. 2, 2009, and entitled "Electronically Controlled Marking Apparatus and Methods;" which are incorporated by reference herein in their entirety.

It will be understood that the docking stations described herein can be used with other marking devices, including but not limited to marking devices that have limited electronic capability and marking devices that have no electronic capability. In some embodiments, the docking station may be used for holding, storage and/or locking of the marking device, without electronic functionality. In addition, the docking station may be used for docking of a combination locate and marking device, which includes both locate and marking functions.

Marking device **150** may include a shaft **154**, a handle **158**, a marking dispenser holder **162**, an actuator **166**, control electronics **170**, at least one rechargeable battery **172** for powering control electronics **170**, a docking station interface **174**, and an RFID tag **178**. Rechargeable battery **172** may be a power source for the marking device **150**. Rechargeable batteries **172** may be, for example, rechargeable lithium ion batteries, which are sized according to the requirements of control electronics **170**. RFID tag **178** may store a unique identification code, which may be used to identify and track marking device **150**.

A marking dispenser **180** (e.g., an aerosol marking paint canister) may be installed in marking dispenser holder **162** of marking device **150** as illustrated. Actuator **166** may be an electrical/mechanical actuator for activating the marking material spray action of marking dispenser **180**.

Control electronics **170** may include, but is not limited to, a processor, GPS technology, RFID technology, data storage devices, electronic actuator, electronic display, marking material sensing technology and wired and/or wireless communications technology (e.g., an Intranet connection, Internet, Bluetooth® technology, Wi-Fi, Wi-Max, IEEE 802.11 technology, radio frequency (RF), Infrared Data Association (IrDA) compatible protocols, Local Area Networks (LAN), Wide Area Networks (WAN), Shared Wireless Access Protocol (SWAP), combinations thereof, and other types of wireless networking protocols).

Docking station interface **174** is a mechanism that is designed to fit cradle **118** of docking station **100** to provide a mechanical and electrical connection therebetween. The physical dimensions and shape of docking station interface **174** of marking device **150** substantially correspond to the physical dimensions and shape of cradle **118** of docking station **100**. Furthermore, electrical inputs/outputs (I/Os) (e.g., signal, data, and power), integrated into docking station interface **174**, are designed to connect to their counterparts

integrated in cradle **118** of docking station **100**. An example of docking station interface **174** of marking device **150** is described with reference to FIGS. **5A**, **5B**, **6A**, **6B**, and **7**.

FIG. **2** is a schematic diagram of marking device **150** attached to docking station **100**, according to embodiments of the invention. More specifically, FIG. **2** depicts marking device **150** resting and retained within a cavity of base **110** of docking station **100**. Docking station interface **174** of marking device **150** is engaged with cradle **118** of docking station **100**. Docking station **100** can be configured to dock marking device **150** either with or without marking dispenser **180** installed in marking device **150**. Safety strap **142** may be fastened around shaft **154** of marking device **150** to hold marking device **150** securely, so that the marking device remains mechanically and electrically coupled to docking station **100**.

The docking station **100** shown in FIGS. **1** and **2** and described above provides both mechanical and electronic docking of a marking device. In particular, the docking station **100** is mechanically coupled to the marking device **150** in the docked position and has docking station electronics **128** which communicate electronically with control electronics **170** in marking device **150**. It will be understood, however, that the docking station may have a variety of configurations within the scope of the present invention.

Referring to FIG. **3A**, a block diagram of an electronic docking station **200** is shown. Docking station **200** includes docking control electronics coupled by an electronic connection **206** to a marking device **202**. Electronic connection **206** may be a wired connection, such as by a cable or electrical connector, or may be a wireless connection. Embodiments of docking control electronics for docking station **200** are described below. Docking station **200** may be connected to a computing device **204** via an electronic connection **208**, which may be a wired connection or a wireless connection. The computing device **204** may be an on-site computer, such as an in-vehicle computer, or may be a remote computer, such as a central office computer. Docking station **200** provides electronic support of marking device **202** and supports such functions as data storage and/or transfer, battery charging and diagnostics and calibration, for example. However, docking station **200** is not mechanically coupled to marking device **202** and does not provide mechanical support, storage or locking of marking device **202**. The physical configuration of docking station **200** may be an electronics enclosure or housing having suitable connectors, cables and/or antennas for communication with marking device **202** and computing device **204**, and optional user interface components as described below.

Referring to FIG. **3B**, a docking station **210** is mechanically and electronically coupled to a marking device **212**. An electronic connection **216** between docking station **210** and marking device **212** may be a wired connection, such as by a cable or electrical connector, or may be a wireless connection between docking station electronics and marking device electronics. Docking station **210** further includes a mechanical connection **217** to marking device **212**. Mechanical connection **217** may have a variety of configurations, including, but not limited to, a holder to support and retain marking device **212**, a locking mechanism that is mechanically or electronically controlled and/or a partial or complete enclosure for marking device **212**. The partial or complete enclosure for the marking device may provide security for the marking device and/or may protect the marking device against exposure to weather conditions. The docking station **210** may provide mechanical support for marking device **212** in any desired position, such as vertical or horizontal, for example, and may

be fixed or mobile. Docking station **210** may include an electronic connection **218** to a computing device **214**, which may be local or remote as described above in connection with computing device **204**. Electronic connection **218** may be a wired connection or a wireless connection. The docking station **100** shown in FIGS. **1** and **2** may be of the type shown in FIG. **3B**.

Referring to FIG. **3C**, a docking station **220** is mechanically coupled to a marking device **222** by a mechanical connection **227**. The mechanical connection between docking station **220** and marking device **222** may have any desired mechanical configuration, including but not limited to a holder to support and retain marking device **222** in a desired orientation, such as vertical or horizontal, a locking mechanism to secure marking device **222** to docking station **220** and/or a partial or complete enclosure for marking device **222**. The partial or complete enclosure for the marking device may provide security for the marking device and/or may protect the marking device against exposure to weather conditions. In the embodiment of FIG. **3C**, an electronic connection is not provided between docking station **220** and marking device **222**. Marking device **222** may communicate directly with a computing device **224** via an electronic connection **228**, which may be a wired connection or a wireless connection. Computing device **224** may be a local computer, such as an in-vehicle computer or may be a remote computer, such as a central office computer. The physical configuration of docking station **220** may be similar to docking station **100** shown in FIGS. **1** and **2**, with most or all electronic components omitted.

In each of FIGS. **3A**, **3B** and **3C**, the electronic connection to the computing device is optional. The computing device may provide control of the docking station and may receive marking device data, such as data from electronic records of marking operations. The marking device data may be transferred by the docking station from the marking device directly to the computing device and/or may be stored in a local memory of the docking station. The data transfer may occur at the time of docking of the marking device or may occur at a later time, such as at the end of the day. In other embodiments, the electronic connection between the docking station and the computing device is omitted. For example, data can be transferred from the docking station to any desired computing device by use of a removable memory.

In the embodiments of FIGS. **3A**, **3B** and **3C**, the docking station may provide a battery charging function for the marking device. Thus, for example, the docking station can be connected to a power source, such as an AC power source for fixed applications, or a DC source, such as vehicle power, for mobile applications. The docking station may include circuitry for charging batteries in the marking device. In other embodiments, a separate battery charger is connected directly to the marking device.

A block diagram of docking control electronics **250** in accordance with embodiments of the invention is shown in FIG. **4**. Docking control electronics **250** may include components for managing the overall operation of the docking stations described herein. Docking control electronics **250** may include a communication interface **252** for communication with a marking device, a communication interface **254** for communication with a local or remote computing device, and a user interface **256** for interacting with a user by receiving user inputs and/or providing information to a user. Docking control electronics **250** may further include a timing system **260** for timing of docking station operations and events, a location tracking system **262** for determining geographical

coordinates of the docking station and an ID reader **264** for reading an identification tag **265** on the marking device.

Docking control electronics **250** may further include a processor **266** and at least one memory **270**. Memory **270** may be used for storage of control software and for data storage. It will be understood that memory **270** may be configured as one or more memories, such as separate memories for data storage and program storage. Memory **270** may include a data storage area **290** for storage of data transferred from the marking device and/or other data involved in operation of the docking station.

Docking control electronics **250** may further include a battery control circuit **272** which receives AC or DC power from an external power source **274** and performs charging of the battery of the marking device under control of processor **266**.

In some embodiments, docking control electronics **250** may include a memory connector (not shown) to permit connection of a memory device, such as a memory device containing data from the marking device. In further embodiments, docking control electronics **250** may include a battery connector (not shown) to permit connection of one or more batteries from the marking device, for charging.

Control software, typically stored in memory **270**, may include a communication control module **280** to control communication with the marking device and with the computing device, and a data transfer module **282** to perform data transfer to and between the marking device, a local memory and the computing device. The control software may further include a battery control module **284** to control battery charging and recording of battery information, a diagnostics module **286** to perform diagnostics and calibration of the marking device, as well as diagnostics of the docking station itself. The control software may further include a security module **288** that controls a locking mechanism and/or data transfer operations based on information including, but not limited to, a table of approved marking device IDs, allowed and prohibited geographical coordinates and/or allowed and prohibited times and dates.

Communication interface **252** may be any wired and/or wireless communication interface by which information may be exchanged between the docking station and a marking device. Similarly, communication interface **254** may be any wired and/or wireless communication interface by which information may be exchanged between the docking station and a local or remote computing device. Examples of wired communication interfaces may include, but are not limited to, USB ports, RS232 connectors, RJ45 connectors, Ethernet, and combinations thereof. Examples of wireless communication interfaces may include, but are not limited to, Bluetooth® Technology, Wi-Fi, Wi-Max, IEEE 802.11 Technology, Radio Frequency (RF), Local Area Networks (LAN) and Wide Area Networks (WAN), Internet, Shared Wireless Access Protocol (SWAP), Infrared Data Association (IrDS) compatible protocols and other types of wireless networking protocols, and combinations thereof.

User interface **256** may be any mechanism or combination of mechanisms by which the user may interact with the docking station. For example, user interface **256** may include, but is not limited to, a display (including integrated displays and external displays, such as Heads-Up Displays (HUDs)), a touch screen, one or more manual pushbuttons, one or more toggle switches, a keypad, and combinations thereof. In one example, the display includes one or more liquid crystal displays (LCD) or light-emitting diode (LED) displays that are suitably small for use in a portable device yet suitably large for ease of viewing. User interface **256** may include standard

zoom in and out controls for the display. In one example, a display includes a 4.3 inch diagonal LCD. Preferably, the display is at least 5 characters tall by 40 characters wide, is full-sun daylight readable and includes automatic backlighting for low light applications. In one implementation, the user interface **256** includes a “menu/on” button to power up the docking station and provide a menu-driven graphical user interface (GUI) displayed by the display device (e.g., menu items and/or icons displayed on the display device) and navigated by the technician via a joystick or a set of four “up/down/left/right” buttons, as well as a “select/ok” button to take some action pursuant to the selection of a menu item/icon. In further implementations, the user interface may include a microphone and the processor may be configured to accept and process audible commands, such that docking station operations may be accomplished via voice-activated commands by simply speaking into the microphone.

Additionally, user interface **256** may include one or more indicators such as, for example, LED indicators, audio devices, such as a speaker, a buzzer and/or an alarm, and combinations thereof. During normal usage of the docking station, the components of user interface **256** may be used to display, for example, the current status of the docking station, the current status of the docked marking device, alerts and notifications and option selections.

Timing system **260** may include an internal clock, such as a crystal oscillator device, for processor **266**. Additionally, timing system **260** may include a mechanism for registering time with a specified degree of accuracy, such as accuracy to the minute, second or millisecond. Timing system **260** may also include a mechanism for registering the calendar date. Using timing system **260**, a timestamp may be appended to any information that is handled by the docking station, such as for example marking device data, time of docking the marking device, time of undocking the marking device, time of battery charging, and the like. In some embodiments, timing system **260** may register the time and date using its internal clock. In other embodiments, timing system **260** may receive time and date information from location tracking system **262**. In further embodiments, timing system **260** may receive time and date information from an external timing system, such as a remote computer or network, via communication interface **254**.

Location tracking system **262** may include any device that can determine geographical coordinates to a specified degree of accuracy. For example, location tracking system **262** may include a Global Positioning System (GPS) receiver or a Global Navigation Satellite System (GNSS) receiver. A GPS receiver may provide, for example, any standard format data stream, such as a National Marine Electronics Association (NMEA) data stream. The location tracking system **262** may include an error correction component which may be a mechanism for improving the accuracy of the geographical coordinates provided by the location tracking system **262**. In one example, the error correction component may include an algorithm for correcting offsets, such as due to local disturbances in the atmosphere, in the geographical coordinates provided by location tracking system **262**. Using location tracking system **262**, geographical coordinates can be recorded and/or transmitted for any docking station operation or information.

In another embodiment, location tracking system **262** may include a device or mechanism that determines location such as by performing triangulation by the use of cellular telephone towers.

ID reader **264** includes a mechanism for short range identification of the ID tag **265** which may be affixed to the

marking device. ID reader **264** may be a radio frequency identification (RFID) reader for reading an RFID tag affixed to the marking device. In another embodiment, ID reader **264** may include a barcode reader for reading a barcode tag affixed to the marking device. The ID reader **264** typically reads the ID tag **265** when the marking device is docked in the docking station.

Processor **266** may be any general purpose processor, controller or microcontroller device that is capable of managing the overall operations of the docking station as described herein. The processor **266** may include a single processing device or more than one processing device.

Memory **270** may comprise any computer-readable media and may store computer instructions for implementing the various functions described herein as well as any data associated with operation of the docking station. The processor **266** may be used to execute the stored instructions. Memory **270** may include volatile and/or non-volatile data storage media and/or data storage devices. For example, memory **270** may be, but is not limited to, a random access memory (RAM), a read-only memory (ROM) and/or a removable memory device, such as a USB flash memory.

As indicated above, communication control module **280** includes software for controlling communication interface **252** to communicate with the marking device and for controlling communication interface **254** to communicate with a local or remote computing device. The communication may be associated with any function of the docking station, including but not limited to data transfer, control of the marking device, battery charging, diagnostics and calibration, for example. As indicated above, the communication with the marking device may be by wired connection or may be wireless. Further, the communication with the computing device may be by wired connection or may be wireless.

Data transfer module **282** controls data transfer to and between the marking device, the docking station and the local or remote computing device. Marking device data may be transferred from the marking device to data storage **290** in memory **270** for later transfer to the computer device. In other embodiments, data transfer module **282** is configured to control data transfer between the marking device and the computing device without temporary storage in data storage **290**. In further embodiments, data transfer module **282** is configured to control data transfer from the docking station to the marking device. The data may be transferred to the marking device from data storage **290** and/or from the computing device. By way of example only, the data transferred to the marking device may define some or all parameters of a marking operation to be performed by the marking device.

In some embodiments, data transfer module **282** may be configured to provide data backup for the marking device. By copying marking device data to the local memory in the docking station and/or to the local or remote computing device at specified times, data integrity and data security are provided, even if the marking device is damaged, lost or stolen. For example, data can be copied from the marking device to the docking station upon completion of a marking operation or a part thereof, or at specified intervals.

Data transfer module **282** may ensure synchronization of data between the marking device and data storage **290** as described below. Data transfer module **282** may perform functions such as format conversion, data compression and the like, related to data communication. In some embodiments, data storage **290** may be a removable memory component, such as a USB flash memory, that is physically removed from the docking station and installed in the local or remote computing device for data transfer.

Battery control module **284** may control monitoring and charging of one or more batteries in the marking device by battery control circuit **272**. The battery control module **284** may determine the charge state of the one or more batteries in the marking device and, if necessary, initiate and control battery charging. The battery control module, in conjunction with timing system **260**, may be configured to record a date and time of battery charging. The battery control module **284**, in conjunction with location tracking system **262**, may be configured to record geographical coordinates of the battery charging operation. The battery control module **284** may be configured to determine and/or record various parameters of the one or more batteries in the marking device, including but not limited to battery quality and/or battery capacity.

Diagnostics module **286** may be configured to perform diagnostics of the marking device. In particular, diagnostics module **286** may place the marking device in a diagnostics mode and may execute a diagnostics routine on the marking device. The diagnostics routine may include sending stimulus signals to the marking device and receiving responses or lack thereof which indicate the operational state of the marking device. The diagnostics routine may test some or all of the components of the marking device.

Diagnostics module **286** may also perform calibration of one or more components of the marking device. For example, when a component of the marking device provides a response that does not meet specification, the component may be adjusted by appropriate signals sent by the diagnostics module **286** to meet specification.

Diagnostics module **286** may also be configured to perform self-diagnostics of the docking station. In this case, diagnostics module **286** may place the docking station in a diagnostics mode and may execute a diagnostics routine for testing some or all components of the docking station. The result of the diagnostics routine can be recorded and/or transmitted to the local or remote computing device.

The diagnostics module **286**, in conjunction with timing system **260**, may be configured to record a time and date when a diagnostics and/or calibration routine was performed. Diagnostics module **286**, in conjunction with location tracking system **262**, may be configured to record the geographical coordinates where a diagnostics and/or calibration routine was performed. The recording of diagnostics information may be important in establishing that the marking device and/or the docking station was functioning properly at a particular time and date and/or location.

Security module **288** may be configured to control various security components and functions of the docking station. In some embodiments, security module **288** may be configured to receive the ID of the marking device from ID reader **264** and compare the ID of the marking device with a list of approved marking device IDs. If the ID of the marking device does not match one of the approved marking device IDs in the list, operation of the docking station may be modified and/or terminated. For example, an alert can be generated by the docking station and/or an alert can be transmitted to the local or remote computing device. Furthermore, operations such as data transfer, battery charging and the like can be terminated when the ID of the marking device does not match an approved marking device ID.

In other embodiments, security module **288** may be configured to receive a user ID from user interface **256**, such as via a keypad or other input device, and compare the user ID with a list of approved user IDs. In the absence of a match between the user ID and one of the approved user IDs, operation of the docking station can be modified or terminated and an alert can be generated as described above.

In further embodiments, security module **288** may be configured to control a locking mechanism, such as a safety strap, a locking bar or other locking device. The locking mechanism may secure the marking device or may secure an enclosure for the marking device, such as for example a weatherproof enclosure. Thus, for example, security module **288** may be configured to maintain the locking mechanism in a locked state if the user ID does not match one of the approved user IDs. In further embodiments, security module **288** may be configured, in conjunction with timing system **260**, to maintain the locking mechanism in a locked state at specified times and dates, such as, for example, during nighttime, weekends and holidays. In further embodiments, security module **288** may be configured, in conjunction with location tracking system **262**, to maintain the locking mechanism in a locked state when the docking station is outside specified geographical coordinates, is at specified geographical coordinates, or is within specified geographical coordinates. The specified geographical coordinates may indicate a location or area where removal of the marking device from the docking station is not permitted.

In further embodiments, the security module **288** may be configured to generate a user alert or notification when a marking device is not present in the docking station. Presence or lack of presence of the marking device may be detected, for example, by a sensor switch. In other embodiments, the security module **288** may be configured to generate a user notification or alert when the marking device is present in the docking station but is not secured in the docking station, for example, the marking device is not properly positioned or the locking mechanism is not engaged. In further embodiments, security module **288** may be configured to respond to a security command from a local or remote computing device. The security command may cause the security module **288** to terminate operations, to engage any locking mechanism and/or to shut down, for example.

It will be understood that the above described components and functions of the docking station may be utilized separately or in any combination. Furthermore, various components of the docking control electronics **250** shown in FIG. 4 and described above may be omitted from the docking station, within the scope of the invention. As noted above, battery charging may be a separate function not included in the docking station. The docking station, for example, may not include ID reader **264**, timing system **260** and/or location tracking system **262** in particular applications and configurations. In some embodiments, the docking station may be controlled by the computing device, in which case, all or part of user interface **256** may be omitted. Depending on the configuration, various software modules may be omitted, and in other embodiments, additional software modules may be included in the docking station. As described above, some embodiments of the docking station may include minimal or no electronics, in which case the docking station serves as a holder for the marking device.

FIGS. 5A and 5B are top and side views, respectively, of a portion of docking station **100**. FIGS. 5A and 5B illustrate that cradle **118** is recessed into the upper end of support housing **114**. Additionally, a female alignment feature **310** is provided within cradle **118** and is recessed into support housing **114**. Male connector pins **314** are arranged within female alignment feature **310**, to which electrical signals and power are connected. The number, type, and arrangement of male connector pins **314** may vary according to the requirements of docking station **100**. The dimensions of cradle **118** and female alignment feature **310** may vary according to the requirements of docking station **100**.

FIGS. 6A and 6B are side and bottom views, respectively, of a portion of marking device 150. FIG. 7 is a side view of marking device 150 being attached to docking station 100. Docking station interface 174 of marking device 150 is designed to fit into cradle 118 of docking station 100. Accordingly, FIGS. 6A and 6B show that the geometry of docking station interface 174 is complementary to the geometry of cradle 118 of FIGS. 5A and 5B. For example, the body of docking station interface 174 is designed to fit within the recessed area of cradle 118. Further, a male alignment feature 410 is integrated into docking station interface 174. Male alignment feature 410 is designed to fit within the recessed female alignment feature 310 of cradle 118 shown in FIGS. 5A and 5B. A set of female connector pins 414 are arranged within male alignment feature 410, to which electrical signals and power are connected. The number, type, and arrangement of female connector pins 414 may vary according to the requirements of marking device 150 and docking station 100. Female connector pins 414 of marking device 150 are arranged to substantially align with the arrangement of male connector pins 314 of docking station 100. As a result, when marking device 150 is attached to docking station 100, male connector pins 314 fit into female connector pins 414 of marking device 150, providing an electrical connection therebetween, as shown in FIG. 7.

While FIGS. 5A, 5B, 6A, and 6B describe a pin and hole type of connection (e.g., male connector pins 314 fitting into female connector pins 414) between docking station 100 and marking device 150, this connection is exemplary. Those skilled in the art will recognize that any type of electrical connection mechanism may be used, such as, but not limited to, an induction coupling mechanism. In addition, the mechanical and electrical coupling between docking station 100 and marking device 150 can be at any convenient location on the two devices, with complementary elements on the two devices to facilitate coupling and decoupling. Furthermore, the mechanical and electrical coupling elements can be combined, as shown in FIGS. 5A, 5B, 6A, 6B and 7, or can be separate coupling elements.

As illustrated in FIG. 7, docking station interface 174 of marking device 150 fits into cradle 118 of docking station 100. In particular, male alignment feature 410 of docking station interface 174 having female connector pins 414 is aligned with and fit into female alignment feature 310 of cradle 118 that has male connector pins 314.

FIG. 8A is a top view of an exemplary configuration incorporating docking station 100. More specifically, FIG. 8A is a top view of a configuration incorporating docking station 100 in a vehicle cab 600 of the type typically used in the field. Vehicle cab 600 may include both a driver seat 610 and a passenger seat 614, which are facing a dash 618. In this mounting configuration, docking station 100 may be mounted to the back wall of vehicle cab 600 (i.e., the wall opposite dash 618) in a location that is substantially centralized between driver seat 610 and passenger seat 614 for ease of access. For example, docking station 100 may be secured to the back wall of vehicle cab 600 by use of security screws to prevent the unauthorized removal of docking station 100. Docking station 100 is positioned to face the front (i.e., toward dash 618) of vehicle cab 600 to allow for easy attachment and removal of marking device 150.

Docking station 100 may be wired directly into a vehicle's power system. Docking station 100 thus receives power simultaneously with other vehicle components (when the key is in the accessory, power, start, or run position), and powers down upon vehicle power off. In one embodiment, the design and construction of docking station 100 provides a power line

and a ground line. Both lines may be spliced into, for example, a restraint control module 622 that is typically located directly under passenger seat 614 of the vehicle. As a result, docking station 100 receives power when restraint control module 622 receives power. Docking station 100 provides a battery charging mechanism for marking device 150 via the combination of the vehicle power and docking control electronics 128. In another embodiment, the docking station may charge the marking device at any time (including accessory, power, start, run or off positions), for example, at preset times before the beginning of a shift to ensure that the marking device is fully charged, or for a period of time after the vehicle is shut off at the end of a shift.

Additionally, FIG. 8A shows an onboard computer 626 within vehicle cab 600. Onboard computer 626 may be any computing device, such as, but not limited to, any laptop computer, handheld computer or onboard server that is capable of executing software applications related to operations of docking station 100 and marking device 150. In particular, there may be a wired connection, such as wired connection 140, between docking station 100 and onboard computer 626. In an embodiment, onboard computer 626 communicates with marking device 150 via a wireless communication link when within range. Also, when marking device 150 is attached to docking station 100, docking station 100 provides a wired communications link between onboard computer 626 and marking device 150. The type of information that may be exchanged between onboard computer 626 and marking device 150 may include, but is not limited to, marking data, timing data, GPS data, RFID data, status data, health data, software, and firmware updates, diagnostics information, and the like.

FIG. 8B is a top view of another embodiment incorporating docking station 100. In this mounting configuration, docking station 100 may be securely fastened to the floor of vehicle cab 600 in place of a passenger seat. In an embodiment, docking station 100 is securely bolted to the floor of vehicle cab 600 using, for example, a set of existing passenger seat bolt holes 630 in the floor of vehicle cab 600. Optionally, a mounting plate 634 may be provided at base 110 of docking station 100 for bolting to bolt holes 630. As depicted in FIG. 8B, a passenger seat is not present and restraint control module 622 may be located underneath the cab floor covering. As previously discussed, the power line and ground lines of docking station 100 may be spliced into restraint control module 622. Additionally, a USB or similar connection may be provided between docking station 100 and onboard computer 626. This mounting configuration allows docking station 100 to be installed without drilling additional holes in the floor of vehicle cab 600. As a result, docking station 100 is positioned in place of the passenger seat and may be oriented to allow easy access through the passenger door of vehicle cab 600.

FIGS. 8A and 8B illustrate embodiments where the docking station is mounted within a vehicle cab. It will be understood that the docking station can be mounted in any convenient location in a vehicle. For example, docking station may be mounted in the bed of a truck, in the rear of a van, within a panel truck or trailer, or in any other desired location. Further, the docking station can retain the marking device in any desired orientation, such as vertical, horizontal or any other desired orientation. In addition, any number of docking stations can be mounted in a vehicle.

In some embodiments, the docking station may include a weatherproof enclosure for the marking device. The weatherproof enclosure may be beneficial, for example, when the docking station is exposed to the weather, such as in the bed

of a truck. The weatherproof enclosure may also provide enhanced security and may include a locking mechanism.

FIG. 8C is a functional block diagram of a network system 650 that includes the mobile docking station 100. More specifically, network system 650 includes one or more mobile docking stations 100 and one or more associated marking devices 150. Each mobile docking station 100 of network system 650 may be connected to onboard computer 626 of the vehicle in which it is installed, as shown in FIGS. 8A and 8B. In another embodiment, onboard computer 626 may be any on-site computer, and is not limited to a computer in a vehicle. Additionally, each onboard computer 626 or other on-site computer of network system 650 may be connected to a remote computing device, such as remote computer 654. Remote computer 654 may be a centralized computer, such as a central server of, for example, the locate service provider.

In order to facilitate the network connection, each onboard computer 626 or other on-site computer includes a communication link 658. Likewise, remote computer 654 includes a communication link 662. Communication link 658 and communication link 662 may be any wired and/or wireless communication interface by which information may be exchanged. Examples of wired communication interfaces may include, but are not limited to, USB ports, RS232 connectors, RJ45 connectors, Ethernet, and any combinations thereof. Examples of wireless communication interfaces may include, but are not limited to, an Intranet connection, Internet, Bluetooth® technology, Wi-Fi, Wi-Max, IEEE 802.11 technology, radio frequency (RF), Infrared Data Association (IrDA) compatible protocols, Local Area Networks (LAN), Wide Area Networks (WAN), Shared Wireless Access Protocol (SWAP), combination thereof, and other types of wireless networking protocols. The wireless interface may be capable of capturing signals that reflect a user's intent. For example, the wireless interface may include a microphone that can capture a user's intent by capturing the user's audible commands. The wireless interface may also interact with a device that monitors a condition of the user, such as eye movement, brain activity, and/or heart rate.

FIG. 9 is a flow diagram of a method 700 of using a docking station according to embodiments of the invention. In particular, FIG. 9 is a flow diagram of method 700 of synchronizing the data of, for example, marking device 150 with a local or remote computer, such as onboard computer 626, when detected in docking station 100. Method 700 may include, but is not limited to, the following acts, which are not limited to any order.

In act 710, the docking station receives power. For example, when docking station 100 is installed in a vehicle, as shown in FIGS. 8A and 8B, docking station 100 receives direct current (DC) power when the vehicle key is in the accessory, power, start, or run position.

In act 714, it is determined whether a marking device 150 is present in the docking station 100. For example, using software of onboard computer 626, queries of docking station 100 may be performed in order to determine the presence or absence of marking device 150. In one embodiment, onboard computer 626 may query the RFID reader of docking station 100 in order to determine whether RFID data is returned. More specifically, when marking device 150 is present in docking station 100, RFID data is returned from its RFID tag 178 to onboard computer 626 by the RFID reader 129 of docking station 100. By contrast, when marking device 150 is not present in docking station 100, no RFID data is returned to onboard computer 626 from docking station 100.

In another example, a logic state may be returned from docking control electronics 128, depending upon whether an

electrical connection exists between docking station 100 and marking device 150 (e.g., between male connector pins 314 of docking station 100 and female connector pins 414 of marking device 150). This may be referred to as "docking pin awareness." Other methods of determining whether a marking device is present in the docking station are possible, such as pressure sensors and any number of other solutions. If it is determined that marking device 150 is present in docking station 100, method 700 proceeds to act 718. If it is determined that marking device 150 is not present in docking station 100, method 700 ends.

In act 718, it is determined whether a data synchronization operation is needed between the marking device and the local or remote computer. Data synchronization is the process by which the local or remote computer receives data that was not previously exchanged between the marking device and the local or remote computer. For example, using software of onboard computer 626, it may be determined whether a data synchronization operation is needed between marking device 150 and onboard computer 626. For example, onboard computer 626 interrogates the data (e.g., marking data, timing data, GPS data, RFID data, and the like) that may be stored on marking device 150 and checks a flag, such as a send/acknowledge flag, to determine whether a packet of data was transmitted and received successfully. When the expected flags are present, onboard computer 626 skips over that packet of data in order to avoid collecting duplicate data. Any data that was not successfully transmitted and/or received is transmitted from marking device 150 to onboard computer 626 (or remote computer via wireless communication) via the USB or similar connection between docking station 100 and onboard computer 626. If it is determined that a data synchronization operation is needed, method 700 proceeds to act 722. If it is determined that a data synchronization operation is not needed, method 700 ends.

In act 722, a data synchronization operation is performed between the marking device 100 and the remote or local computer. For example, a data synchronization operation is performed between marking device 150 and onboard computer 626 via the USB connection between docking station 100 and onboard computer 626. Once the data is synchronized, method 700 ends.

Referring again to method 700 of FIG. 9, docking station 100 communicates with onboard computer 626 and, if appropriate, may begin synchronizing data immediately when marking device 150 is detected in docking station 100. Alternatively, a manual control 134, such as the "initiate data synchronization" push button of docking station 100 allows the operator to manually perform synchronization at any time. Also, data synchronization may occur automatically upon the docking of the marking device.

A data synchronization operation is described above in connection with FIG. 9. It will be understood that communication between docking station 100 and marking device 150 may include any control and/or data transfer function, including but not limited to issuing commands to marking device 150, receiving status and other operating information from marking device 150, downloading ticket information and other operating parameters, uploading information of any type, performing diagnostics, and the like.

FIG. 10 is a flow diagram of another method of using a docking station. In particular, FIG. 10 is a flow diagram of a method 800 of managing the indicators and/or manual controls of docking station 100 when a marking device, such as marking device 150, is detected therein. Method 800 informs the user of status changes and other conditions that may

require attention. Method **800** may include, but is not limited to, the following acts, which are not limited to the following order.

In act **810**, the docking station receives power. For example, when docking station **100** is installed in a vehicle, as shown in FIGS. **8A** and **8B**, docking station **100** receives DC power when the vehicle key is in the accessory, power, start, or run position.

In act **814**, it is determined whether a marking device is present in the docking station. For example, if it is determined that marking device **150** is not present in docking station **100**, method **800** proceeds to act **818**. If it is determined that marking device **150** is present in docking station **100**, method **800** proceeds to act **822**. The presence or absence of marking device **150** in docking station **100** may be determined as described above in connection with FIG. **9**.

In act **818**, indicators **130** are set to show that no marking device is present and certain manual controls are disabled. For example, a red battery status indicator and a red synchronization status indicator may be turned on, and the initiate data synchronization push button may be deactivated.

In act **822**, it is determined whether the power source, for example, a battery, of marking device **150** needs charging. For example, onboard computer **626** interrogates control electronics **170** of marking device **150** in order to determine the health status of rechargeable batteries **172**. If it is determined that rechargeable batteries **172** of marking device **150** do not need charging, method **800** proceeds to act **826**. If it is determined that rechargeable batteries **172** of marking device **150** do need charging, method **800** proceeds to act **830**.

In act **826**, an indicator **130** is set to show battery status=charged. For example, a green battery status indicator may be turned on. Method **800** proceeds to act **834**.

In act **830**, an indicator **130** is set to show battery status=charging. For example, a yellow battery status indicator may be turned on and caused to blink. Alternatively, in the case of total battery failure, a red battery failure indicator may be turned on in order to show a defective battery in marking device **150**.

In act **834**, it is determined whether a data synchronization operation is needed between the marking device and the local or remote computer. For example, if it is determined that a data synchronization operation is needed, method **800** proceeds to act **838**. However, if it is determined that a data synchronization operation is not needed, method **800** proceeds to act **850**. The need for a synchronization operation may be determined as described above in connection with FIG. **9**.

In act **838**, an indicator **130** is set to show synchronization is in progress. For example, an orange synchronization status indicator may be turned on and caused to blink. In act **842**, it is determined whether a data synchronization error condition is present. For example, onboard computer **626** determines whether a data synchronization error condition has been identified. If a data synchronization error condition is not present, method **800** returns to act **838**. If a data synchronization error condition is present, method **800** proceeds to act **846**.

In act **846**, an indicator **130** is set to show whether a data synchronization error condition is present. For example, a red synchronization error indicator may be turned on and caused to blink. In act **850**, it is determined whether the initiate data synchronization push button of docking station **100** has been pushed. For example, onboard computer **626** interrogates docking control electronics **128** of docking station **100** to determine the status thereof. If it is determined that the initiate data synchronization push button has been pushed, method **800** proceeds to act **838**. If it is determined that the initiate

data synchronization push button has not been pushed, method **800** then proceeds to act **854**.

In act **854**, an indicator **130** is deactivated. For example, the orange synchronization status indicator may be turned off.

FIG. **11** is a schematic diagram of a marking device attached to a docking station. In particular, FIG. **11** depicts a side view of marking device **150** attached to docking station **100**. Docking station **100** further includes a locking mechanism **910**. In addition to safety strap **142**, marking device **150** may be lockable within a vehicle via the optional locking mechanism **910** of FIG. **11**. In one embodiment, locking mechanism **910** may be a suitably rigid, strong, and tamper-proof bracket (e.g., hinged bracket) that is installed on support housing **114**. Locking mechanism **910** may include a switch or lever (not shown) to ensure that marking device **150** is properly secured within docking station **100** during driving (i.e., for safety) in the event of an accident, as well as to ensure proper charging and data transfer. A keyed lock, such as a padlock, may be used to secure marking device **150** against theft.

FIG. **12** is a flow diagram of a method of using a docking station. In particular, FIG. **12** illustrates a method **1000** of notifying the user of the presence and security of the marking device in docking station **100**. Method **1000** may provide an audible means of informing the user of the presence and security of marking device **150** in docking station **100**. Method **1000** may include, but is not limited to, the following acts, which are not limited to the following order.

In act **1010**, it is determined whether docking station **100** is receiving power. For example, when docking station **100** is installed in a vehicle, such as shown in FIGS. **8A** and **8B**, docking station **100** receives DC power when the vehicle key is in the accessory, power, start, or run position. If onboard computer **626** determines that vehicle power is present, method **1000** proceeds to act **1014**. If onboard computer **626** determines that vehicle power is not present, method **1000** ends.

In act **1014**, it is determined whether a marking device **150** is present within the docking station. For example, if it is determined that marking device **150** is not present in docking station **100**, method **1000** proceeds to act **1018**. If it is determined that marking device **150** is present in docking station **100**, method **1000** proceeds to act **1022**. The presence or absence of marking device **150** in docking station **100** may be determined as described above in connection with FIG. **9**.

In act **1018**, an audible notification is generated to the user that the marking device **150** is absent from the docking station **100** within the vehicle. For example, a buzzer (via audio output **138** of docking station **100**) may be triggered until the vehicle is shut off or until marking device **150** is placed in docking station **100**. Thus, it may be ensured that the user returns marking device **150** to the vehicle after each use. Method **1000** then returns to act **1014**.

In act **1022**, it is determined whether the marking device is secure within the docking station **100**. For example, onboard computer **626** determines the status of safety strap **142** and/or the switch or lever of locking mechanism **910** in order to determine whether such items are in a secure state. If it is determined that marking device **150** is secure in docking station **100**, method **1000** ends. If it is determined that marking device **150** is not secure in docking station **100**, method **1000** proceeds to act **1026**.

In act **1026**, an audible notification is generated, indicating to the user that the marking device is not secure in docking station **100** within the vehicle. For example, a buzzer (via audio output **138** of docking station **100**) may be triggered until the vehicle is shut off or until marking device **150** is

placed in docking station **100**. This ensures that marking device **150** is physically secure in the vehicle while the vehicle is moving. Method **1000** then returns to act **1022**.

FIG. **13** is a schematic diagram of an exemplary configuration incorporating docking stations. In particular, FIG. **13** is a schematic diagram of a bank of one or more docking stations **1100**, which may be fixed and suitable for use with at least one marking device. For example, FIG. **13** shows a home base facility **1110** at which a bank of docking stations **1100** are installed along a wall **1114**. In another configuration, the bank of docking stations **1100** may be installed on the floor or a table. Each docking station **1100** may be substantially the same as docking station **100** as depicted in FIGS. **1** through **12**, except that its power source may be designed and constructed to utilize an alternating current (AC) power source (e.g., an AC power source **1118**), instead of the DC power of a vehicle. A shielded power cord terminated in a three (3) prong plug may be used. The bank of docking stations **1100** may also be powered by direct current (DC) power sources. Like docking station **100**, each docking station **1100** allows a marking device, such as marking device **150**, to be attached and detached easily for charging and, where applicable, for data synchronization.

Each docking station **1100** is designed and constructed to be mounted against a fixed structure such as a wall. In addition, each docking station **1100** is designed and constructed of materials that prevent unauthorized removal thereof. The bottom of each docking station **1100** may be flat in order to allow for placement on the floor of a building or on a table. Each docking station **1100** may be affixed to the floor and/or wall using security screws to prevent the unauthorized removal of the docking station. A variety of attachment means may be used to affix docking stations **1100**. In addition, each docking station **1100** may be positioned to allow the easy attachment and removal of a marking device.

Docking station **100** and where applicable, docking station **1100**, may support the synchronization of the marking device to a local or remote computer, such as a remote computer **1122**, which may be, for example, a host server. This synchronization may be performed through the use of a USB cable. Upon attachment of the marking device, each docking station **1100** may determine whether or not data synchronization is necessary and, if it is, perform substantially the same data synchronization process that is shown in method **700** of FIG. **9** and described above.

The status indicators and device controls of each docking station **1100** may be substantially the same as those of docking station **100**. A method of managing the indicators and/or manual controls of each docking station **1100** may be substantially the same as method **800** of FIG. **10** for docking station **100**.

In another embodiment, each docking station **1100** may include a cleaning mechanism at the base thereof for cleaning any components that may be installed at the marking dispenser holder end of a marking device. An example of a cleaning mechanism may be a compact ultrasonic cleaning station that utilizes cleaning fluid, such as, but not limited to, isopropyl alcohol.

FIGS. **14**, **15**, and **16** are perspective views of another embodiment of the docking station according to the present invention. FIG. **14** depicts a docking station **1200** for docking a marking device **1250**. Docking station **1200** may be an example of another embodiment of both docking station **100** and docking station **1100**, which may be in a variety of locations in fixed or mobile configurations.

In this embodiment of the docking station, docking station **1200** may include a base **1210**, a support housing **1214**, and a

cradle **1218**. The functions of base **1210**, support housing **1214**, and cradle **1218** are substantially the same as the functions of base **110**, support housing **114**, and cradle **118**, respectively, of FIGS. **1** through **13**. Docking station **1200** of FIGS. **14**, **15**, and **16** differs primarily from docking station **100** and docking station **1100** of FIGS. **1** through **13** in its physical attributes.

In this embodiment of the docking station, marking device **1250** may include a shaft **1254**, a handle **1258**, a marking dispenser holder **1262** and a docking station interface **1274**. The functions of shaft **1254**, handle **1258**, marking dispenser holder **1262**, and docking station interface **1274** are substantially the same as the functions of shaft **154**, handle **158**, marking dispenser holder **162** and docking station interface **174**, respectively, of FIGS. **1** through **13**. Marking device **1250** of FIGS. **14**, **15**, and **16** differs primarily from marking device **150** of FIGS. **1** through **13** in its physical attributes. In particular, in this embodiment, docking station interface **1274** is incorporated on the side of shaft **1254** that is opposite handle **1258**. By contrast and referring to FIG. **1**, docking station interface **174** of marking device **150** is incorporated on the same side of shaft **154** as handle **158**.

With reference to FIGS. **14** and **16**, respectively, marking device **1250** is shown separated from and attached to docking station **1200**. FIG. **15** shows further details of docking station **1200**. More specifically, FIG. **15** shows an alignment feature **1222** of cradle **1218** that provides the electrical and mechanical coupling to a corresponding alignment feature (not visible) of docking station interface **1274** of marking device **1250**.

Additional security features may be incorporated into the docking stations described herein (e.g., docking station **100**, docking station **1100** and docking station **1200**). For example, in addition to the physical locking mechanism, the docking stations may be equipped with a positive identification mechanism. This positive identification mechanism (not shown) is provided to ensure that the user is authorized to remove the marking device from the docking station. This mechanism may include biometric, RFID, passcode, or any other means of positively identifying the user. For example, using intelligence that may be incorporated into docking stations, in order to unlock the marking device, the user may be prompted to provide input that validates that he/she is authorized to use the marking device. In the event that the proper credentials are supplied, the locking mechanism of the docking station releases the marking device to the user. If improper credentials are supplied, the docking station may enter a security lockdown mode, trigger a remote alert to a supervisor of the user, and/or trigger an audible or visible alarm indicating that it is not available for use.

In this embodiment, the docking stations may not allow the user to remove the marking device until positive identification, as explained above, has been provided. In this embodiment, the biometric, RFID, passcode or any other means shall be a feature of the docking stations and provide enhanced security to the physical locking measures (e.g., strap and padlock) already described.

In an embodiment and with regard to docking station **100**, an audible security alarm may be tied into existing vehicle alarms, such as an alarm that sounds when the key is left in the ignition when the user opens the door, when the lights are left on or when the user opens the door and so on. Alternatively, the vehicle may be disabled from starting if marking device **150** is not properly secured in docking station **100**.

In another embodiment and with regard to docking stations **1100** and **1200**, a supervisor of a user may view (e.g., using a graphical user interface (GUI) of remote computer **1122**) the

status of docking stations **1100** and **1200**, such as whether a marking device **150** is present and properly secured or not.

The docking stations of the present invention (e.g., docking station **100**, docking station **1100**, and docking station **1200**) are not limited to use with a portable marking device. The docking stations may be suitable for use with other types of portable devices. In an embodiment, the docking stations described herein may accommodate and function with a locate device or similar instrument for detecting facilities. Moreover, the docking stations described herein may also accommodate and function with a combination marking and locate device.

FIG. **17** is a perspective view of a marking device docking station **1300** that has processing and communications capability. Docking station **1300** may be installed in, for example, a vehicle and is suitable for use in conjunction with a marking device, such as marking device **1350**. In other embodiments, docking station **1300** may be installed at a central facility, office or other fixed location. Thus, docking station **1300** may be mobile or fixed. Docking station **1300** may serve as a home base for storage of marking device **1350** and for charging the battery of marking device **1350**. Marking device **1350** is, for example, an electronic marking device. In one example, marking device **1350** may be based on the electronic marking devices that are described above in connection with marking device **150**.

Docking station **1300** may include a base **1310** and a body **1312**. Additionally, a cradle **1314** is integrated into the upper end of body **1312** (the end opposite base **1310**). Cradle **1314** provides a means to mechanically and electrically couple marking device **1350** to docking station **1300**. Base **1310**, body **1312**, and cradle **1314** may be made of any suitably strong, rigid, and lightweight material, such as, but not limited to, molded plastic and metal. Additionally, docking station **1300** may include a security mechanism **1316** for holding and securing marking device **1350** into cradle **1314** in a lockable manner. For example, security mechanism **1316** may be a flexible strap or a rigid bracket that may be placed around the body of marking device **1350** and secured with a locking mechanism (not shown) to docking station **1300**.

Docking station **1300** may also include control electronics for providing processing and communications capability to docking station **1300**. For example, docking station **1300** may include control electronics **1320** that includes a processing unit **1322**, a local memory **1324**, a communication interface **1326**, a presence detection mechanism **1328**, a security detection mechanism **1330**, and, optionally, a location tracking system **1332**.

Processing unit **1322** may include any standard controller or microprocessor device that is capable of executing program instructions. Local memory **1324** may be any data storage mechanism for storing any information that is processed locally at docking station **1300**. Processing unit **1322** and local memory **1324** may be used for managing the overall operations of docking station **1300**.

Communication interface **1326** may include any wired and/or wireless communication interface for connecting to a network (not shown) and by which information may be exchanged with other computing devices that may be separate from docking station **1300** and/or with other docking stations **1300**. Examples of wired communication interfaces may include, but are not limited to, USB ports, RS232 connectors, RJ45 connectors, Ethernet, and any combinations thereof. Examples of wireless communication interfaces may include, but are not limited to, an Intranet connection, Internet, Bluetooth® technology, Wi-Fi, Wi-Max, IEEE 802.11 technology, radio frequency (RF), Infrared Data Association (IrDA)

compatible protocols, Local Area Networks (LAN), Wide Area Networks (WAN), Shared Wireless Access Protocol (SWAP), any combinations thereof, and other types of wireless networking protocols.

Presence detection mechanism **1328** may include any mechanism of control electronics **1320** that is capable of determining whether a marking device **1350** is present within cradle **1314**. In one example, presence detection mechanism **1328** may be a radio frequency identification (RFID) reader that is able to read, for example, an RFID tag **1334** that is affixed to marking device **1350**. When marking device **1350** is present in cradle **1314**, the RFID reader is able to read information (e.g., a marking device ID) from RFID tag **1334**, which indicates that marking device **1350** is present in docking station **1300**. However, when marking device **1350** is not present in cradle **1314**, the RFID reader is unable to read information from RFID tag **1334**, which indicates that marking device **1350** is not present in docking station **1300**.

In another example, presence detection mechanism **1328** may include circuitry for reading the state of a “presence signal,” which may be an electronic signal that has one state (e.g., a logic high) when marking device **1350** is present and another state (e.g., a logic low) when marking device **1350** is not present. The “presence signal” may be generated based, for example, upon sensing an electrical connection (or not) between docking station **1300** and marking device **1350** at the interface of cradle **1314**.

Security detection mechanism **1330** may include any mechanism of control electronics **1320** that is capable of determining whether security mechanism **1316** is engaged around marking device **1350** and locked. For example, presence detection mechanism **1328** may include circuitry for reading the state of a “locked signal,” which may be an electronic signal that has one state (e.g., a logic high) when security mechanism **1316** is engaged and locked and another state (e.g., a logic low) when security mechanism **1316** is not engaged and locked.

In one example, the locking mechanism of security mechanism **1316** may include an electromagnetic locking mechanism (not shown) that may be engaged/disengaged by a user of docking station **1300**. In this example, the “locked signal” may be generated based upon sensing the state of the electromagnetic locking mechanism. In another example, the locking mechanism of security mechanism **1316** may include an electromechanical locking mechanism (not shown) that may be engaged/disengaged by a user of docking station **1300**. Again, the “locked signal” may be generated based upon sensing the state of the electromechanical locking mechanism.

Location tracking system **1332**, which is optional in docking station **1300**, may include any device that can determine its geographical location to a specified degree of accuracy. For example, location tracking system **1332** may include a global positioning system (GPS) receiver or a global navigation satellite system (GNSS) receiver. A GPS receiver may provide, for example, any standard format data stream, such as a National Marine Electronics Association (NMEA) data stream. Location tracking system **1332** may also include an error correction component (not shown), which may be any mechanism for improving the accuracy of the geo-location data.

With respect to docking station **1300** being a recharging station for one or more batteries (not shown) of marking device **1350**, docking station **1300** may include power management electronics **1340**. When marking device **1350** is present in docking station **1300**, power management electronics **1340** provides a standard battery charging function. Power

management electronics **1340** is also able to communicate to control electronics **1320** the charging state of the one or more batteries of marking device **1350**, for example, 50% charged, 75% charged, and so on.

Optionally, receptacles may be integrated into base **1310** of docking station **1300** for accepting rechargeable batteries **1342**, which may be spare rechargeable batteries for use in marking device **1350**. In one example, FIG. **1** shows two receptacles for accepting two rechargeable batteries **1342**. When at least one rechargeable battery **1342** is present in base **1310**, power management electronics **1340** provides a standard battery charging function. Power management electronics **1340** is also able to communicate to control electronics **1320** the presence of and the charging state of any rechargeable batteries **1342**.

In operation, under the control of processing unit **1322**, any information acquired and/or generated by docking station **1300** may be stored in local memory **1324**. For example, information about the presence and security of marking device **1350** at docking station **1300** may be logged in local memory **1324**. Information about the charging state of the one or more batteries of marking device **1350** may be logged in local memory **1324**. Information about the charging state of any rechargeable batteries **1342** in base **1310** may be logged in local memory **1324**. The geo-location data from location tracking system **1332** may be logged in local memory **1324**, and the like.

Additionally, when marking device **1350** is present in docking station **1300**, any information about locate operations (hereafter called marking data) that is stored in marking device **1350** may be transferred from marking device **1350** to local memory **1324** of docking station **1300**.

With respect to any of the aforementioned information, whether originating from docking station **1300** or from marking device **1350**, communication interface **1326** may be used to exchange information between docking station **1300** and any other computing devices that may be separate from docking station **1300**. Additionally, communication interface **1326** may be used to exchange information between docking station **1300** and any other docking stations **1300**. Further, when, for example, marking device **1350** is in use in the field (i.e., not docked), communication interface **1326** may be used to exchange information wirelessly between docking station **1300** and marking device **1350**. Docking station **1300** may communicate information regardless of whether a marking device **1350** is present. Examples of marking device docking station configurations and networks are described with reference to FIGS. **18** through **21**.

FIG. **18** is a schematic diagram of a docking station network **1400**, which is one example of a docking station network. In this example, docking station network **1400** may include multiple fixed marking device docking stations **1300** in communication with a central computing device.

In particular, FIG. **18** shows a bank of one or more docking stations **1300**, which may be fixed and suitable for use with at least one marking device **1350** at, for example, a home base facility. The bank of docking stations **1300** may be floor-mounted along a wall **1410**, as shown in FIG. **18**. In another configuration, the bank of docking stations **1300** may be hung on a wall, free-standing on the floor, free-standing on a table, and any combinations thereof. In this configuration, the power source for each docking station **1300** may be designed and constructed to utilize an alternating current (AC) power source (e.g., an AC power source **1412**). For example, a shielded power cord terminated in a three (3) prong plug may be used. The bank of docking stations **1300** may also be powered by direct current (DC) power sources (not shown).

Each docking station **1300** allows a marking device, such as marking device **1350**, to be attached and detached easily for charging and, where applicable, for data transfer.

In the configuration of docking station network **1400**, the one or more docking stations **1300** are in communication with a central computing device. The central computing device may be, for example, a central control panel **1414** and/or a central server **1416**. Docking stations **1300** may communicate with central control panel **1414** and/or central server **1416** via their respective communication interfaces **1326**. Further, the communication of each docking station **1300** may be managed by its processing unit **1322**. Central control panel **1414** and/or central server **1416** may be used to collect information from docking stations **1300**, such as, but not limited to, marking device presence information, marking device security information, marking device battery status information, spare battery status information, marking data of marking devices, and the like. The information returned from docking stations **1300** may be useful, for example, for monitoring marking device inventory, monitoring marking device battery status, monitoring marking device security, monitoring spare battery inventory and status, collecting marking data, and so on.

By way of example and referring again to FIG. **18**, by using the processing and communications capabilities of docking stations **1300a** through **1300g**, central control panel **1414** and/or central server **1416** may determine, log, and report the following.

- a) no marking device **1350** is present in docking station **1300a**, two rechargeable batteries **1342** are present in docking station **1300a**, the first rechargeable battery **1342** is 100% charged, the second rechargeable battery **1342** is 100% charged;
- b) no marking device **1350** is present in docking station **1300b**, no rechargeable batteries **1342** are present in docking station **1300b**;
- c) no marking device **1350** is present in docking station **1300c**, one rechargeable battery **1342** is present in docking station **1300c**, the rechargeable battery **1342** is 78% charged;
- d) a marking device **1350d** is present in docking station **1300d**, marking device **1350d** is locked down and secure, the batteries of marking device **1350d** are 100% charged, two rechargeable batteries **1342** are present in docking station **1300d**, the first rechargeable battery **1342** is 100% charged, the second rechargeable battery **1342** is 100% charged;
- e) a marking device **1350e** is present in docking station **1300e**, marking device **1350e** is locked down and secure, the batteries of marking device **1350e** are 67% charged, two rechargeable batteries **1342** are present in docking station **1300e**, the first rechargeable battery **1342** is 82% charged, the second rechargeable battery **1342** is 74% charged;
- f) no marking device **1350** is present in docking station **1300f**, no rechargeable batteries **1342** are present in docking station **1300f**;
- g) a marking device **1350g** is present in docking station **1300g**, marking device **1350g** is not locked down and secure, the batteries of marking device **1350g** are 100% charged, two rechargeable batteries **1342** are present in docking station **1300g**, the first rechargeable battery **1342** is 100% charged, the second rechargeable battery **1342** is 94% charged;

- h) three of a possible seven marking devices **1350** are present and accounted for, two of the three present are fully charged, one of the three present is not fully charged; and
- i) ten of a possible fourteen rechargeable batteries **1342** are present and accounted for, five of the ten present are fully charged, five of the ten present are not fully charged.

FIG. **19** is a schematic diagram of a docking station network **1500**, which is another example of a docking station network. In this example, docking station network **1500** may include multiple mobile marking device docking stations **1300** in the field and in communication with an onsite computing device. More specifically, FIG. **19** shows multiple vehicles **1510**, such as a vehicle **1510a**, **1510b**, and **1510c**. Installed in each vehicle **1510** is a docking station **1300**. For example, installed in vehicles **1510a**, **1510b**, and **1510c** are docking stations **1300a**, **1300b**, and **1300c**, respectively. Vehicles **1510a**, **1510b**, and **1510c** may be, for example, the vehicles of locate technicians that are dispatched to a jobsite in the field. Docking stations **1300a**, **1300b**, and **1300c** are used to hold marking devices (not shown) in vehicles **1510a**, **1510b**, and **1510c**. In this configuration, the power source for each docking station **1300** may be designed and constructed to utilize the DC power of a vehicle. Alternatively, instead of multiple docking stations **1300** in multiple vehicles **1510**, there may be multiple docking stations **1300** in a one vehicle **1510**.

In the configuration of docking station network **1510**, the one or more docking stations **1300** are in communication with a central computing device. In one example, the central computing device may be an onsite computer **1520**. Onsite computer **1520** may be any onsite computing device, such as, but not limited to, a laptop computer, a handheld computer, and a tablet device, that has network capability. In particular, onsite computer **1520** is capable of communicating with any docking stations **1300** within its range. In one example, onsite computer **1520** may be present in one of the vehicles **1510**.

As described with reference to FIG. **18**, by using the processing and communications capabilities of docking stations **1300a**, **1300b**, and **1300c**, onsite computer **1520** may determine, log, and report, for example, marking device presence, marking device battery status, marking device security, spare battery presence and status, marking data from each marking device, and so on.

FIG. **20** is a schematic diagram of a docking station network **1600**, which is yet another example of a docking station network. In this example, docking station network **1600** may include multiple mobile marking device docking stations **1300** in the field and in communication with each other. Docking station network **1600** is substantially the same as docking station network **1500** of FIG. **19**, except that the multiple docking stations **1300** are communicating directly with each other instead of to a central computing device, such as onsite computer **1520** of FIG. **19**.

With respect to docking station network **1600**, any docking station **1300** may poll any other docking station **1300** to determine their status (i.e., peer-to-peer communication). This may be accomplished using communication interface **1326** of each docking station **1300**, which may have short range wireless communication capability, such as Bluetooth®.

The configuration of docking station network **1600** may be useful, for example, to implement certain protocols with respect to performing locate operations. In one example, a project ticket calls for two locate technicians. Therefore, two vehicles **1510** with two docking stations **1300** (holding two

marking devices), respectively, are present at the jobsite. In this example, a software rule may be implemented that once the locate operation is complete, the marking devices **1350** must be present in the respective docking stations **1300** before any data from either marking device **1350** is processed and before the ticket can be classified as complete. In order to accomplish this, there is communication between the two docking stations **1300** as to the presence of their respective marking devices **1350** and no data can be transferred until both are present. This may be useful to ensure a complete set of data to accompany the completed project ticket (i.e., eliminating any chance of partial data). Further, this scenario may ensure the association of data of the two marking devices involved. Any removal of either marking device in the middle of data transfer is communicated between the two docking stations **1300**, which will stop data transfer of the remaining marking device.

FIG. **21** is a schematic diagram of a docking station network **1700**, which is still another example of a docking station network. In this example, docking station network **1700** may include at least one marking device docking station **1300** in communication with at least one marking device **1350**.

Docking station network **1700** is an example of using communication interface **1326** of docking station **1300** to exchange information wirelessly with a marking device **1350**. The configuration of docking station network **1700** may be useful, for example, to implement certain protocols with respect to performing locate operations. In one example, docking station **1300** may receive a message from an external system via, for example, onsite computer **1520** of FIG. **19**. This message is then flashed from docking station **1300** to its associated marking device **1350**. The user of marking device **1350** receives the message at his/her marking device **1350** and may respond accordingly.

The various methods or processes outlined herein may be coded as software that is executable on one or more processors that employ any one of a variety of operating systems or platforms. Additionally, such software may be written using any of a number of suitable programming languages and/or programming or scripting tools, and also may be compiled as executable machine language code or intermediate code that is executed on a framework or virtual machine.

In this respect, various inventive concepts may be embodied as a computer readable storage medium (or multiple computer readable storage media) (e.g., a computer memory, one or more floppy discs, compact discs, optical discs, magnetic tapes, flash memories, circuit configurations in Field Programmable Gate Arrays or other semiconductor devices, or other tangible computer storage medium) encoded with one or more programs that, when executed on one or more computers or other processors, perform methods that implement the various embodiments of the invention discussed above. The computer readable medium or media can be transportable, such that the program or programs stored thereon can be loaded onto one or more different computers or other processors to implement various aspects of the present invention as discussed above.

The terms “program” or “software” are used herein in a generic sense to refer to any type of computer code or set of computer-executable instructions that can be employed to program a computer or other processor to implement various aspects of embodiments as discussed above. Additionally, it should be appreciated that according to one aspect, one or more computer programs that when executed perform methods of the present invention need not reside on a single computer or processor, but may be distributed in a modular fash-

ion amongst a number of different computers or processors to implement various aspects of the present invention.

Computer-executable instructions may be in many forms, such as program modules, executed by one or more computers or other devices. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Typically the functionality of the program modules may be combined or distributed as desired in various embodiments.

Also, data structures may be stored in computer-readable media in any suitable form. For simplicity of illustration, data structures may be shown to have fields that are related through location in the data structure. Such relationships may likewise be achieved by assigning storage for the fields with locations in a computer-readable medium that convey relationship between the fields. However, any suitable mechanism may be used to establish a relationship between information in fields of a data structure, including through the use of pointers, tags or other mechanisms that establish relationship between data elements.

Also, various inventive concepts may be embodied as one or more methods, of which an example has been provided. The acts performed as part of the method may be ordered in any suitable way. Accordingly, embodiments may be constructed in which acts are performed in an order different than illustrated, which may include performing some acts simultaneously, even though shown as sequential acts in illustrative embodiments.

All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

The indefinite articles “a” and “an,” as used herein in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean “at least one.”

The phrase “and/or,” as used herein in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

As used herein in the specification and in the claims, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the claims, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used herein shall only be interpreted as indicating exclusive alternatives (i.e. “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Con-

sisting essentially of,” when used in the claims, shall have its ordinary meaning as used in the field of patent law.

As used herein in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

In the claims, as well as in the specification above, all transitional phrases such as “comprising,” “including,” “carrying,” “having,” “containing,” “involving,” “holding,” “composed of,” and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases “consisting of” and “consisting essentially of” shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

What is claimed is:

1. A docking station for docking a marking device used to mark a presence or an absence of an underground facility in a dig area, the docking station comprising:

a housing configured to mechanically support the marking device in a docked position, wherein the housing is configured for mounting in or on a vehicle; and
a security mechanism to secure the marking device in the docking station, wherein the security mechanism comprises at least one of:

- 1) a locking device configured to lock the marking device to the docking station;
- 2) an ID mechanism to enable removal of the marking device from the docking station in response to verification of the identity of a user; and
- 3) a safety strap for securing the marking device to the docking station.

2. A docking station as defined in claim 1, wherein the housing is configured to support the marking device in a storage position.

3. A docking station as defined in claim 1, wherein the housing includes an alignment element to facilitate docking of the marking device.

4. A docking station as defined in claim 1, wherein the security mechanism is configured to control removal of the marking device from the docking station.

5. A docking station as defined in claim 1, wherein the security mechanism comprises the locking device configured to lock the marking device to the docking station.

6. A docking station as defined in claim 1, wherein the security mechanism comprises the ID mechanism to enable removal of the marking device from the docking station in response to verification of the identity of the user.

31

7. A docking station as defined in claim 1, wherein the security mechanism comprises the safety strap for securing the marking device to the docking station.

8. A docking station as defined in claim 1, wherein the housing defines a compartment configured to at least partially enclose the marking device in the docking station.

9. A docking station as defined in claim 1, wherein the housing is configured to mechanically support a combination marking and locate device.

10. A docking station as defined in claim 1, wherein the housing includes a base to retain a lower portion of the marking device.

11. A docking station as defined in claim 1, wherein the housing includes a support member to support an upper portion of the marking device.

12. A docking station as defined in claim 1, wherein the housing includes a cradle for mechanical coupling to the marking device, the cradle including an electrical connector for providing electrical connections between the docking station and the marking device.

13. A docking station as defined in claim 1, wherein the housing is configured for mounting to a back wall of a vehicle cab.

14. A docking station as defined in claim 1, wherein the housing is configured for mounting in a vehicle cab in place of a passenger seat.

32

15. A docking station as defined in claim 1, wherein the housing is configured for mounting in a bed of a truck.

16. A docking station as defined in claim 1, further comprising a wired interface for a connection to vehicle power.

17. A docking station as defined in claim 1, configured to supply power from the vehicle to the marking device.

18. A docking station as defined in claim 1, further comprising a power interface to recharge a battery in the marking device.

19. A docking station as defined in claim 1, further comprising a cleaning device configured to clean the marking device.

20. A docking station as defined in claim 1, wherein the housing is configured to mechanically support the marking device in a vertical orientation.

21. A docking station as defined in claim 1, wherein the housing is configured to mechanically support the marking device in a horizontal orientation.

22. A docking station as defined in claim 1, wherein the housing is configured for mobile use of the docking station.

23. A docking station as defined in claim 1, wherein the housing is configured for use of the docking station in a fixed location.

* * * * *